

Motorbike Fork Oil 5W light

Description

Fully synthetic fork and shock absorber oil with optimized responsiveness. Also includes suitability for the fork oil requirement SAE 4W through SAE 2.5W. Prevents the formation of foam and the hardening of seals. Offers good corrosion and wear protection for high operating reliability.

Properties

- exceptionally sensible responsiveness
- can be used up to fork oil requirement SAE 2.5W with regard to viscosity and viscosity characteristics
- lasting corrosion protection
- prevents foam formation
- increases driving safety
- high wear resistance
- prevents seals from swelling

Technical data

Density at 15 °C	0,825 g/cm ³ DIN 51757
Viscosity at 40 °C	18 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	4,1 mm ² /s ASTM D 7042-04
Viscosity index	131 DIN ISO 2909
Pour point	-72 °C DIN ISO 3016
Flash point	220 °C DIN ISO 2592
Color number (ASTM)	L 0,5 DIN ISO 2049

Areas of application

Universal use in telescopic forks and shock absorbers on motorbikes, mopeds, motor-assisted bicycles and other two-wheelers.

Application

Note the telescopic fork, shock absorber and two-wheel vehicle manufacturers' instructions.

Available pack sizes

500 ml Can plastic	1523 D-GB-I-E-P
500 ml Can plastic	5950 D-F-I-NL
1 l Can plastic	2716 D-GB-I-E-P
1 l Can plastic	20747 GB-DK-FIN-N-S

Available pack sizes

5 l Canister plastic	1623 D-GB-I-E-P
20 l Canister plastic	3016 D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.

