

Motorbike 4T Bike-Additive

Description

Optimizes the performance of the engine. Removes deposits in the fuel system, on valves, spark plugs and in the combustion chamber and prevents new deposits. This reduces the fuel consumption. Protects the entire fuel system against corrosion. Prevents carburetor icing. Tested on engines with catalytic converters.



Properties

- increases operational reliability
- highly economical
- environmentally friendly
- optimizes engine performance
- tested for the use with catalytic converters
- reduces the risk of knocking combustion
- normalizes gasoline consumption and exhaust emissions
- for carburetor and fuel-injection engines
- reduces residue
- prevents corrosion in the fuel system

legally binding.

Technical data

Base	additive mixture in liquid carrier
Color / appearance	light yellow, clear
Regulation on Flammable Liquids Class (Germany)	A II
Flash point	> 61 °C
Pour point	-45 °C
Form	liquid
Odor	characteristic
Viscosity at 40 °C	<7 mm ² /s
Density at 15 °C	0,7989 g/ml

Areas of application

Add to fuel for all 4-stroke engines (aspirated and injection).

Application

125 ml formulated for 15 – 20 l of fuel. Add every time you refuel.

Available pack sizes

125 ml Can sheet metal	1581
	DE-EN
125 ml Can sheet metal	5918
	DE-FR-IT-NL

Our information is based on thorough research and may be considered reliable, although not