

## Radiator Stop Leak

### Description

Dispersion for sealing leaks in cooling water circuits of water-cooled engines. Reliably seals hairline cracks and smaller leaks. It can also be used preventively as protection after a cooling system repair. The solids dispersion is stabilized in carrier fluid.

### Properties

- compatible with conventional coolants and antifreezes
- suitable for aluminum radiators
- permanently and reliably seals hairline cracks and small leaks
- no negative side effects on the water pump or heating circuit
- for preventive use

### Technical data

Form	liquid
Color / appearance	white, cloudy
Density at 20 °C	1,05 g/cm <sup>3</sup>
Solubility in water	mixable
Odor	weak
Flash point	>100 °C

### Areas of application

Used for sealing small leaks in cooling circuits of passenger cars, commercial vehicles and two-wheelers. Also suited for cooling water circuits equipped with water filters (with the exception of "low conductivity" coolants).

### Comment

Store free of frost.

The treated product contains biocides as protective agents. Contains a mixture of 5-chloro-2-methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1).

### Application

Shake well before use. Add contents to the cold cooling system. Start up the heater. Then drive the vehicle for at least 10 minutes. 250 ml is sufficient for up to 10 l of coolant.

### Available pack sizes

250 ml Can sheet metal	1810
	EL-EN-IT
250 ml Can sheet metal	1921
	DE-FR-IT
250 ml Can sheet metal	2676
	BG-DE-PL

### Available pack sizes

250 ml Can sheet metal	2828
	DA-FI-NO-SV
250 ml Can sheet metal	8370
	AR-EN-FR
250 ml Can sheet metal	8385
	DE-HU-RO
250 ml Can sheet metal	20869
	JA

**Our information is based on thorough research and may be considered reliable, although not legally binding.**

