Product information

Diesel Purge

PI 27/05/13/2024



Description

Removes deposits on injection nozzles and in the combustion chamber. Boosts the cetane number. Eliminates engine running problems such as knocking when idling and ensures smooth and quiet engine running. Protects the entire fuel system against corrosion. Optimizes the emission test values. Can also be used preventively. Clean engines use less fuel and reduce the pollutant emissions.

Properties

- boosts the cetane number
- increases operational reliability
- eliminates diesel knocking
- reduces deposits
- cleans the fuel system
- good corrosion protection
- guarantees optimum combustion
- highly economical

Technical data

Base additives dissolved in carrier fluid

Density at 15 °C 0,82 g/cm³

Color / appearance clear, slightly yellowish to slightly reddish

to stignity read

Flash point 63 °C Regulation on Flammable A III

Liquids Class (Germany)

Pour point -35 °C

Odor characteristic

Form liquid
Viscosity at 40 °C <7 mm²/s

Areas of application

For all diesel engines for preventive use, as well as for problem-related

use on vehicles without in-tank pumps. Recommended application quantity 500 ml.

Application

Preventive use:

Add to diesel fuel according to the inspection intervals.

Remedial use:

Disconnect fuel feed and return lines and insert into the diesel purge. Start the engine. Run the engine at a



variety of different speeds and switch off before the container is empty. Reconnect fuel lines to the fuel system and check for leaks. In cases of extreme contamination, repeat the cleaning process if necessary.

Available pack sizes

500 ml Can sheet metal 1811 GB-GR-I 500 ml Can sheet metal 2186 D-H-R0 500 ml Can sheet metal 2509

D-E-P

500 ml Can sheet metal 2666 D-PL-BG

500 ml Can sheet metal 2790 GB-AUS

500 ml Can sheet metal 2813 DK-N-S-FIN

500 ml Can sheet metal 5170 D-F-NL

500 ml Can sheet metal 8380

GB-ARAB-F

500 ml Can sheet metal 20809

D-GB-SLO-SRB-HR

1 l Can sheet metal 2520

D-GB-I-E-P

5 l Canister plastic 2525

D-GB-I-E-P

50 l Black plate barrel 2524

D-GB

205 l Black plate barrel 2528

D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.

Phone: +49 (0)731/1420-0 Fax: +49 (0)731/1420-82 e-mail: info@liqui-moly.de