Product information

Leichtlauf Performance 10W-40



Description

Low-friction motor oil for gasoline and diesel engines, with and without exhaust gas turbocharging and charge air cooler. Protects against wear, reduces oil and fuel consumption and ensures fast oil penetration of the engine.

Total base number 10,3 mg KOH/g DIN ISO 3771

PI 29/02/04/2025

Sulfate ash 0,9 - 1,5 g/100g

Color number (ASTM) L 4,0

DIN ISO 2049

Areas of application

Technical data

For gasoline and diesel engines with and without charge air cooling. Suitable for extended oil change intervals and high engine loads.

Application

The specifications and instructions from the assembly or vehicle manufacturer must be followed. Optimum effectiveness only when the product is used unmixed.

Available pack sizes

Available pack sizes	
1 l Canister plastic	2338 BOOKLET
4 l Canister plastic	8998 BOOKLET
5 l Canister plastic	2536 BOOKLET
20 l Canister plastic	2537 D-GB
60 l Black plate barrel	2101 D-GB
205 l Black plate barrel	2102 D-GB
1.000 l Container	21581 D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.

Properties

- high lubrication reliability
- high shear stability
- instant lubrication after cold start
- optimum stability to aging
- excellent high and low temperature behavior
- smooth engine running
- outstanding engine cleanliness
- miscible with all commercially available motor oils
- saves fuel and reduces pollutant emissions
- high wear resistance
- tested for turbochargers and catalytic converters

Specifications / Approvals

ACEA A3 • ACEA B3 • API SL

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required:

MB 229.1

Technical data

recillicat uata	
SAE class (engine oils)	10W-40 SAE J300
Density at 15 °C	0,860 g/cm³ DIN 51757
Viscosity at 40 °C	95,0 mm²/s ASTM D 7042-04
Viscosity at 100 °C	14,5 mm²/s

Viscosity at -30 °C (MRV) < 60000 mPas

ASTM D4684

Viscosity at -25 °C (CCS) <= 7000 mPas ASTM D5293

Viscosity index 160

cosity index 160 DIN ISO 2909

HTHS at 150°C >= 3.5 mPas

ASTM D5481

Pour point -36 °C

DIN ISO 3016

ASTM D 7042-04

Evaporation loss (Noack) 10,0 %

ASTM D 5800-08 Method

Phone: +49 (0)731/1420-0 Fax: +49 (0)731/1420-82 e-mail: info@liqui-moly.de

В

Flash point 230 °C

DIN ISO 2592