SAFETY DATA SHEET



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name Castrol Bike Polish

Product code 452572-AT01 BE01 BE02 DE01 GBXX IT01 ITXX SEXX

SDS no. 452572 Product registration 1485274

number

Product type Aerosol.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/ Bike care products.

mixture For specific application advice see appropriate Technical Data Sheet or consult our company

representative.

1.3 Details of the supplier of the safety data sheet

Supplier Nordic Lubricants A/S

Arne Jacobsens Alle 7, 5. 2300 København S

Denmark

Telephone number:+45 70 80 70 54 Fax number:+45 70 24 71 06

E-mail address MSDSadvice@bp.com

1.4 Emergency telephone number

EMERGENCY Carechem: +44 (0) 1235 239 670 (24/7)

TELEPHONE NUMBER

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Flam. Liq. 2, H225

Ingredients of unknown Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 2.5%

toxicity

Ingredients of unknown

Fercentage of the mixture consisting of ingredient(s) of unknown hazards to the aquatic

ecotoxicity environment: 2.5%

Classification according to Directive 1999/45/EC [DPD]

The product is classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification F+; R12

Physical/chemical Extremely flammable.

hazards

Human health hazards Not applicable.

Environmental hazards Not applicable.

See Section 16 for the full text of the R phrases or H statements declared above.

See sections 11 and 12 for more detailed information on health effects and symptoms and environmental hazards.

2.2 Label elements

Product name Castrol Bike Polish Product code 452572-AT01 BE01 Page: 1/11

BE02 DE01 GBXX IT01 ITXX SEXX

Version 4 Date of issue 26 April 2014 Format Denmark Language ENGLISH

SECTION 2: Hazards identification

Hazard pictograms



Signal word Danger

Hazard statements H225 - Highly flammable liquid and vapour.

Precautionary statements

Prevention P280 - Wear protective gloves. Wear eye or face protection.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P241 - Use explosion-proof electrical, ventilating, lighting and all material-handling equipment.

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water or shower.

Storage P235 - Keep cool.

Disposal P501 - Dispose of contents and container in accordance with all local, regional, national and

international regulations.

Hazard symbol or symbols

Indication of danger

Supplemental label

elements

Response

Pressurised container: protect from sunlight and do not expose to temperature exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

Special packaging requirements

Containers to be fitted with child-resistant

fastenings

Tactile warning of danger

Yes, applicable.

Not applicable.

2.3 Other hazards

Other hazards which do not result in classification

Solvent "sniffing" (abuse) or intentional overexposure to vapours can produce serious central nervous system effects, including unconsciousness, and possibly death.

SECTION 3: Composition/information on ingredients

Substance/mixture

Mixture

Propellant. Proprietary performance additives.

Classification

Product/ingredient name	Identifiers	%	67/548/EEC	Regulation (EC) No. 1272/2008 [CLP]	Type
√ydrocarbons, C10-C13, n-alkanes, <2% aromatics		<10	Xn; R65 R66	Asp. Tox. 1, H304	[1] [2]
Butane	REACH #: 01-2119474691-32 EC: 203-448-7 CAS: 106-97-8	>=1 - <5	F+; R12	Flam. Gas 1, H220 Press. Gas Liq. Gas, H280	[2]
Alcohols, tallow, ethoxylated	CAS: 61791-28-4	>=1 - <3	Xn; R22 Xi; R41	Acute Tox. 4, H302 Eve Dam. 1, H318	[1]
Carbon dioxide	EC: 204-696-9 CAS: 124-38-9	>=1 - <5	Not classified.	Press. Gas Comp. Gas, H280	[2]
Paraffin waxes and Hydrocarbon waxes	REACH #: 01-2119488076-30 EC: 232-315-6 CAS: 8002-74-2	>=1 - <5	Not classified.	Not classified.	[2]

See Section 16 for the full text of the R-phrases declared above.

See Section 16 for the full text of the H statements declared above.

Type

Product name Castrol Bike Polish Product code 452572-AT01 BE01 Page: 2/11

BE02 DE01 GBXX IT01 ITXX SEXX

Version 4 Date of issue 26 April 2014 Format Denmark Language ENGLISH

SECTION 3: Composition/information on ingredients

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids

should be held away from the eyeball to ensure thorough rinsing. Check for and remove any

contact lenses.

Skin contact Wash skin thoroughly with soap and water or use recognised skin cleanser. Drench

contaminated clothing with water before removing. This is necessary to avoid the risk of sparks from static electricity that could ignite contaminated clothing. Contaminated clothing is a fire hazard. Contaminated leather, particularly footwear, must be discarded. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get

medical attention if irritation develops.

Inhalation If inhaled, remove to fresh air. Get medical attention if symptoms appear.

Ingestion ont induce vomiting unless directed to do so by medical personnel. Never give anything by

mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Poisoning very unlikely unless deliberate ingestion of large quantities

has occurred. Get medical attention if symptoms occur.

Protection of first-aidersNo action shall be taken involving any personal risk or without suitable training. It may be

dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician Treatment should in general be symptomatic and directed to relieving any effects.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing

media

In case of fire, use water fog, alcohol resistant foam, dry chemical or carbon dioxide

extinguisher or spray.

Unsuitable extinguishing

media

Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture

Fighly flammable liquid and vapour. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard. Bursting aerosol containers may be propelled from a fire at high

speed

Hazardous combustion

products

Combustion products may include the following:

carbon oxides (CO, CO₂) (carbon monoxide, carbon dioxide)

metal oxide/oxides

5.3 Advice for firefighters

Special precautions for

fire-fighters

Fromptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed

containers cool.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Product name Castrol Bike Polish Product code 452572-AT01 BE01 Page: 3/11

BE02 DE01 GBXX

Version 4 Date of issue 26 April 2014 Format Denmark Language ENGLISH

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

immediately contact emergency personnel. No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurised contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Put on appropriate personal protective equipment.

For emergency responders

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and materials for containment and cleaning up

Small spill

Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Contaminated absorbent material may pose the same hazard as the spilt product. Dispose of via a licensed waste disposal contractor.

6.4 Reference to other sections

See Section 1 for emergency contact information.

See Section 5 for firefighting measures.

See Section 8 for information on appropriate personal protective equipment.

See Section 12 for environmental precautions.

See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment. Pressurised container: protect from sunlight and do not expose to temperature exceeding 50°C. Do not pierce or burn, even after use. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing gas. Avoid breathing vapour or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Keep away from ignition sources such as heat/sparks/open flame. - No smoking. Do not spray on a naked flame or any incandescent material. Product contaminated rags, paper or material used to absorb spillages, represent a fire hazard, and should not be allowed to accumulate. Dispose of safely immediately after use.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Keep away from heat and direct sunlight. Separate from oxidising materials. Store and use only in equipment/containers designed for use with this product.

Not suitable

Version 4

Prolonged exposure to elevated temperature

7.3 Specific end use(s)
Recommendations

See section 1.2 and Exposure scenarios in annex, if applicable.

Product name Castrol Bike Polish Product code 452572-AT01 BE01 Page: 4/11

BE02 DE01 GBXX IT01 ITXX SEXX

Date of issue 26 April 2014 Format Denmark Language ENGLISH

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

Product/ingredient name Exposure limit values

Paraffins (petroleum), normal C5-20 Arbejdstilsynet (Denmark).

TWA: 1 mg/m3 8 hours. Issued/Revised: 12/1996 Form: mist and

particles

Butane Arbejdstilsynet (Denmark).

TWA: 1200 mg/m³ 8 hours. Issued/Revised: 12/1996 TWA: 500 ppm 8 hours. Issued/Revised: 12/1996

Carbon dioxide Arbejdstilsynet (Denmark).

TWA: 9000 mg/m³ 8 hours. Issued/Revised: 12/1996 TWA: 5000 ppm 8 hours. Issued/Revised: 12/1996

Paraffin waxes and Hydrocarbon waxes Arbejdstilsynet (Denmark).

TWA: 2 mg/m3 8 hours. Issued/Revised: 12/1996 Form: fume

Whilst specific OELs for certain components may be shown in this section, other components may be present in any mist, vapour or dust produced. Therefore, the specific OELs may not be applicable to the product as a whole and are provided for guidance only.

Recommended monitoring procedures

If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Derived No Effect Level

No DNELs/DMELs available.

Predicted No Effect Concentration

No PNECs available

8.2 Exposure controls

Appropriate engineering controls

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits.

All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained.

Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards. The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

Individual protection measures

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location.

Respiratory protection

Respiratory protective equipment is not normally required where there is adequate natural or local exhaust ventilation to control exposure.

Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Respiratory protective equipment must be checked to ensure it fits correctly each time it is worn. In case of insufficient ventilation, wear suitable respiratory equipment.

Provided an air-filtering/air-purifying respirator is suitable, a filter for particulates can be used. Use filter type P or comparable standard.

Air-filtering respirators, also called air-purifying respirators, will not be adequate under conditions of oxygen deficiency (i.e. low oxygen concentration), and would not be considered suitable where airborne concentrations of chemicals with a significant hazard are present. In these cases air-supplied breathing apparatus will be required.

Provided an air-filtering/air-purifying respirator is suitable, a multiple type of gas filter for organic gases and vapours (boiling point ≤65°C and >65°C) can be used for vapour. Use filter types A

Product name Castrol Bike Polish Product code 452572-AT01 BE01 Page: 5/11

BE02 DE01 GBXX IT01 ITXX SEXX

Version 4 Date of issue 26 April 2014 Format Denmark Language ENGLISH

SECTION 8: Exposure controls/personal protection

with AX or comparable standard.

The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Eye/face protection

Skin protection

Hand protection

Safety glasses with side shields.

General Information:

Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. The correct choice of protective gloves depends upon the chemicals being handled, and the conditions of work and use. Most gloves provide protection for only a limited time before they must be discarded and replaced (even the best chemically resistant gloves will break down after repeated chemical exposures).

Gloves should be chosen in consultation with the supplier / manufacturer and taking account of a full assessment of the working conditions.

Recommended: Nitrile gloves.

Breakthrough time:

Breakthrough time data are generated by glove manufacturers under laboratory test conditions and represent how long a glove can be expected to provide effective permeation resistance. It is important when following breakthrough time recommendations that actual workplace conditions are taken into account. Always consult with your glove supplier for up-to-date technical information on breakthrough times for the recommended glove type. Our recommendations on the selection of gloves are as follows:

Continuous contact:

Gloves with a minimum breakthrough time of 240 minutes, or >480 minutes if suitable gloves can be obtained.

If suitable gloves are not available to offer that level of protection, gloves with shorter breakthrough times may be acceptable as long as appropriate glove maintenance and replacement regimes are determined and adhered to.

Short-term / splash protection:

Recommended breakthrough times as above.

It is recognised that for short-term, transient exposures, gloves with shorter breakthrough times may commonly be used. Therefore, appropriate maintenance and replacement regimes must be determined and rigorously followed.

Glove Thickness:

For general applications, we recommend gloves with a thickness typically greater than 0.35 mm.

It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times. Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers' technical data should always be taken into account to ensure selection of the most appropriate glove for the task.

Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:

- Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.
- Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential.

Product name Castrol Bike Polish Product code 452572-AT01 BE01 Page: 6/11 BE02 DE01 GBXX

IT01 ITXX SEXX

Version 4 Date of issue 26 April 2014 Format Denmark Language ENGLISH (Denmark)

SECTION 8: Exposure controls/personal protection

Skin and body

Use of protective clothing is good industrial practice.

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this

product.

Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

Environmental exposure

controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Container explosion may occur under fire conditions or when heated.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state Aerosol.

Colour Beige.

Odour Characteristic.

Odour threshold Not available.

pH 9.5

Melting point/freezing point Initial boiling point and boiling

range

Not available.

Flash point Not available.

Evaporation rate Not available.

Flammability (solid, gas)

FLAMMABLE.

Upper/lower flammability or

explosive limits

Not available.

Vapour pressureNot available.Vapour densityNot available.Relative densityNot available.

Density 980 kg/m³ (0.98 g/cm³) at 20°C

>3

Solubility(ies) Not miscible in water

Partition coefficient: n-octanol/

Auto-ignition temperature

water

Not available.

Decomposition temperature

Not available.

Viscosity

Not available.

Kinematic: 30 mm²/s (30 cSt) at 20°C

Explosive propertiesNot available.
Oxidising properties
Not available.

9.2 Other information

Aerosol product

Type of aerosol Spray
Heat of combustion

\$\mathbb{Z}266 \text{ kJ/g}\$

No additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity

No specific test data available for this product. Refer to Conditions to avoid and Incompatible

materials for additional information.

10.2 Chemical stability The product is stable.

10.3 Possibility ofhazardous reactions
Under normal conditions of storage and use, hazardous reactions will not occur.
Under normal conditions of storage and use, hazardous polymerisation will not occur.

Product name Castrol Bike Polish Product code 452572-AT01 BE01 Page: 7/11

BE02 DE01 GBXX IT01 ITXX SEXX

Version 4 Date of issue 26 April 2014 Format Denmark Language ENGLISH

SECTION 10: Stability and reactivity

10.4 Conditions to avoid Avoid all possible sources of ignition (spark or flame). High temperatures

10.5 Incompatible materials Reactive or incompatible with the following materials: oxidising materials.

10.6 Hazardous Under normal conditions of storage and use, hazardous decomposition products should not be

decomposition products produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity estimates

Route	ATE value
Not available.	

Information on the likely routes of exposure

Routes of entry anticipated: Dermal, Inhalation.

Potential acute health effects

Inhalation Vapour inhalation under ambient conditions is not normally a problem due to low vapour

pressure.

Ingestion

No known significant effects or critical hazards.

Skin contact

No known significant effects or critical hazards.

Eye contact

No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation Adverse symptoms may include the following:

respiratory tract irritation

coughing

Exposure to high concentrations can cause dizziness, lightheadedness, headache, nausea and

blurred vision. Higher levels may cause unconsciousness.

May be harmful by inhalation if exposure to vapour, mists or fumes resulting from thermal

decomposition products occurs.

IngestionNo specific data.Skin contactNo specific data.

Eye contact Adverse symptoms may include the following:

irritation

Delayed and immediate effects and also chronic effects from short and long term exposure

Inhalation Overexposure to the inhalation of airborne droplets or aerosols may cause irritation of the

respiratory tract.

Ingestion Ingestion of large quantities may cause nausea and diarrhoea.

Skin contact Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis.

Eye contact Potential risk of transient stinging or redness if accidental eye contact occurs.

Potential chronic health effects

GeneralNo known significant effects or critical hazards.CarcinogenicityNo known significant effects or critical hazards.MutagenicityNo known significant effects or critical hazards.Developmental effectsNo known significant effects or critical hazards.Fertility effectsNo known significant effects or critical hazards.

SECTION 12: Ecological information

12.1 Toxicity

Environmental hazards Mot classified as dangerous

12.2 Persistence and degradability

No evidence of biodegradability.

12.3 Bioaccumulative potential

This product is not expected to bioaccumulate through food chains in the environment.

Product name Castrol Bike Polish Product code 452572-AT01 BE01 Page: 8/11

BE02 DE01 GBXX IT01 ITXX SEXX

Version 4 Date of issue 26 April 2014 Format Denmark Language ENGLISH

SECTION 12: Ecological information

12.4 Mobility in soil

Soil/water partition Not available.

coefficient (Koc)

Mobility

Spillages are unlikely to penetrate the soil.

12.5 Results of PBT and vPvB assessment

PBT Not applicable. vPvB Not applicable.

12.6 Other adverse effects

Other ecological information Spills may form a film on water surfaces causing physical damage to organisms. Oxygen

transfer could also be impaired.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Methods of disposal Where possible, arrange for product to be recycled. Dispose of via an authorised person/

licensed waste disposal contractor in accordance with local regulations.

Hazardous waste Yes
European waste catalogue (EWC)

Waste code	Waste designation	
15 01 10*	packaging containing residues of or contaminated by dangerous substances	

However, deviation from the intended use and/or the presence of any potential contaminants may require an alternative waste disposal code to be assigned by the end user.

Packaging

Methods of disposal Pressurised container: protect from sunlight and do not expose to temperature exceeding 50°C. Do not pierce or burn, even after use. Where possible, arrange for product to be recycled.

Do not pierce or burn, even after use. Where possible, arrange for product to be recycled. Dispose of via an authorised person/ licensed waste disposal contractor in accordance with

local regulations.

Special precautions This material and its container must be disposed of in a safe way. Empty containers or liners

may retain some product residues. Do not puncture or incinerate container.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	UN 1950	UN 1950	UN 1950	UN 1950
14.2 UN proper shipping name	AEROSOLS, flammable	AEROSOLS, flammable	AEROSOLS	AEROSOLS, flammable
14.3 Transport hazard class(es)	2	2	2.1	2.1
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.
Additional information	Hazard identification number 23 Tunnel code (D)	-	Emergency schedules (EmS) F-D,S-U	-

14.6 Special precautions for Not available. user

Product name Castrol Bike Polish Product code 452572-AT01 BE01 Page: 9/11

BE02 DE01 GBXX

IT01 ITXX SEXX

Version 4 Date of issue 26 April 2014 Format Denmark Language ENGLISH

SECTION 14: Transport information

ADR/RID Classification

5F

code:

ADN Classification code: 5F

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles Not applicable.

Other regulations

REACH StatusThe company, as identified in Section 1, sells this product in the EU in compliance with the

current requirements of REACH.

United States inventory

(TSCA 8b)

At least one component is not listed.

Australia inventory (AICS)

Canada inventory

Japan inventory (ENCS)

At least one component is not listed. At least one component is not listed.

China inventory (IECSC)

At least one component is not listed.

Korea inventory (KECI)
Philippines inventory

(PICCS)

At least one component is not listed.

(FICCS)

Aerosol dispensers

3

4.9% by mass of the contents are flammable.

National regulations

Statutory Order 517 on

Aerosols

Retail or industrial use.

List of undesirable substances

Not listed

15.2 Chemical Safety Assessment This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by

Road

ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment CSR = Chemical Safety Report DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level

DPD = Dangerous Preparations Directive [1999/45/EC]
DSD = Dangerous Substances Directive [67/548/EEC]

EINECS = European Inventory of Existing Commercial chemical Substances

Product name Castrol Bike Polish Product code 452573

Product code 452572-AT01 BE01 Page: 10/11

BE02 DE01 GBXX IT01 ITXX SEXX

Version 4 Date of issue 26 April 2014 Format Denmark Language ENGLISH

SECTION 16: Other information

ES = Exposure Scenario

EUH statement = CLP-specific Hazard statement

EWC = European Waste Catalogue

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as

modified by the Protocol of 1978. ("Marpol" = marine pollution)
OECD = Organisation for Economic Co-operation and Development

PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RRN = REACH Registration Number

SADT = Self-Accelerating Decomposition Temperature

SVHC = Substances of Very High Concern

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure STOT-SE = Specific Target Organ Toxicity - Single Exposure

TWA = Time weighted average

UN = United Nations

UVCB = Complex hydrocarbon substance VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

Full text of abbreviated H

H220 Extremely flammable gas.

statements H280 Contains gas under pressure

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H318 Causes serious eye damage.

Full text of classifications

[CLP/GHS]

Acute Tox. 4, H302 ACUTE TOXICITY (oral) - Category 4
Asp. Tox. 1, H304 ASPIRATION HAZARD - Category 1

Eye Dam. 1, H318 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1

Flam. Gas 1, H220 FLAMMABLE GASES - Category 1

Press. Gas Comp. Gas, GASES UNDER PRESSURE - Compressed gas

H280

Press. Gas Liq. Gas, H280 GASES UNDER PRESSURE - Liquefied gas

Full text of abbreviated R

phrases

R12- Extremely flammable. R22- Harmful if swallowed.

R65- Harmful: may cause lung damage if swallowed.

R41- Risk of serious damage to eyes.

R66- Repeated exposure may cause skin dryness or cracking.

Full text of classifications

[DSD/DPD]

F+ - Extremely flammable

Xn - Harmful Xi - Irritant

History

Date of issue/ Date of

26/04/2014.

revision

Date of previous issue 28/08/2013.

Prepared by Product Stewardship

▼ Indicates information that has changed from previously issued version.

Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

Product name Castrol Bike Polish Product code 452572-AT01 BE01 Page: 11/11

BE02 DE01 GBXX IT01 ITXX SEXX

Version 4 Date of issue 26 April 2014 Format Denmark Language ENGLISH