



Gulf Formula GVX 5W-30

Passenger Car Motor Oil for Volkswagen Vehicles

Product Description

Gulf Formula GVX 5W-30 is a synthetic engine oil designed to deliver outstanding performance and provide extended oil drain intervals in Volkswagen vehicles running on Ultra Low Sulfur fuel. Its mid SAPS (Sulphated ash, Phosphorous & Sulphur) additive technology helps in prolonging the life and maintaining the efficiency of after exhaust treatment devices such as Diesel Particulate Filters (DPFs) and Gasoline Catalytic Converters apart from providing exceptional deposit & wear protection.

Features & Benefits

- Latest mid SAPS additive technology reduces particulate build-up in DPFs, reduces poisoning and degradation of catalyst to prolong life
- Outstanding thermo-oxidative stability reduces deposits & sludge build-up and aids extended oil life
- Excellent antiwear property protects against engine wear and facilitates longer engine life
- Special formula helps in protecting the engines from Low Speed Pre-Ignition (LSPI) and Timing chain wear issues observed in latest turbocharged Gasoline Direct Injection (GDI) engines
- Excellent low temperature fluidity aids cold start and protects against wear at start-up

Applications

- Recommended for long life service in Europe for Volkswagen gasoline & diesel passenger vehicles meeting Euro 6, Euro 5 & Euro 4 emission norms and requiring VW 504 00/507 00 quality oils
- Fully backward compatible and can be used in Volkswagen vehicles requiring oils meeting earlier generation VW specifications
- Recommended for Mercedes Benz, BMW & Porsche vehicles requiring oils meeting MB 229.31/229.51/229.52, BMW Longlife-04 & Porsche Oil Category C30 specifications
- High performance gasoline and diesel engines in passenger cars and vans with exhaust treatment devices such as particulate filters, catalytic converters etc requiring ACEA C3/ API SP type oils

Specifications, Approvals & Typical Properties

Meets the following Specifications		5W-30
ACEA C3, API SP		X
Mercedes MB 229.31, MB 229.52		X
Has the following Approvals		
BMW Longlife-04		X
Mercedes MB-Approval 229.51		X
Porsche "C30" approval		X
Approved under VW Standard 504 00 and 507 00		X
Typical Properties		
Test Parameters	ASTM Method	Test Values
Viscosity @ 100 °C, cSt	D 445	12.2
Viscosity Index	D 2270	172
Flash Point, °C	D 92	234
Pour Point, °C	D 97	-42
Density @ 15°C, Kg/l	D 1298	0.854

December 2021

Properties mentioned above are typical only and minor variations, which do not affect the product performances, are to be expected in normal manufacturing. The above information is based on past history of the grade only and must not be construed as a guarantee of performance. Follow equipment manufacturer's recommendations for performance level and viscosity grade. The Material Safety Data Sheet for this product is available from your nearest Gulf Distributor.

Teklub Canada Ltd Official Distributor of Gulf Oil International in Canada

The information contained herein is believed to be correct at time of publication. No warranty expressed or implied is given concerning the accuracy of the information of the suitability of the products. Teklub Distribution Inc reserves the right to modify and change its products and specifications without prior notice.

www.gulfoil.ca