

## Linelube C3 5W-30 Fully Synthetic Engine Oil

### Product Description

100% synthetic technology ultra high-performance passenger car engine oil developed from decades of experience in conjunction with original equipment manufacturers. The use of our proprietary base oil technology, along with innovative additive chemistry guarantees long oil life and performance without any compromise of engine reliability.

### Features & Benefits

- Ultra-high performance 100% synthetic mid saps technology
- Stays in viscosity grade for entire drain interval
- Helps prevent dirt and sludge build up to maintain engine responsiveness, reduce vibration and keep engine quiet
- Outstanding oxidation resistance provides very long oil life
- Miscible with all mineral & synthetic engine oils
- Modern day 'universal' performance to cover a variety of cars & light vans

### Specifications

- **API** SN
- **ACEA** C2, C3
- **BMW** LL-04
- **GM / VAUXHALL** DEXOS 2 (INCL. GM-LL-A/B-025)
- **MERCEDES BENZ** MB 229.31, MB 229.51, MB 229.52
- **PEUGEOT/CITROEN** PSA B71 2290
- **VW (VAG)** 505.01 (PD)

### Typical Test Data

Name	Method	Units	Result	Limits
Viscosity Grade	SAE J300	-	5W-30	-
Relative Density @ 15°C	ASTM D4052	g/cm <sup>3</sup>	0.862	-
Kinematic Viscosity @ 40°C	ASTM D445	mm <sup>2</sup> /s	75.00	-
Kinematic Viscosity @ 100°C	ASTM D445	mm <sup>2</sup> /s	12.20	9.3 < 12.5
Viscosity Index	ASTM D2270	-	160	-

Pour Point	ASTM D97	°C	-45	-27 MAX
Flash Point (CoC)	ASTM D92	°C	215	-
TBN – Total Base Number	ASTM D2896	mgKOH/g	7.8	6.0 MIN
Appearance	ASTM D4176-1	-	Clear & Bright	-
Colour	Visual	-	Amber	-

## Health & Safety

For health and safety information please refer to the relevant health & safety data sheet on our website. The contents of this data sheet is given in good faith but without warranty.