

Linelube Agri UTTO

Product description

Linelube Agri UTTO is a modern Universal Tractor Transmission Oil for transmissions, hydraulics, final drives and wet brake systems. The very latest agricultural machinery in the modern intensive farming environment needs the protection of a high quality lubricant. Multi-purpose oils are a good compromise but many manufacturers have realised the benefits of using lubricants specifically designed for a given application

Linelube UTTO is blended from carefully selected mineral base oils and the very latest in additive technology to produce a specialised lubricant to meet the latest and most severe transmission requirements. It meets the demands of most agricultural transmission specifications and greatly reduces wet brake noise and chatter. It offers outstanding anti-wear performance under the most severe conditions

Features and Benefits

- · Superior oxidation stability
- Outstanding rust and corrosion protection
- Excellent wet brake, anti-squawk and chatter suppression
- Exceptional anti-wear and extreme pressure properties
- Excellent high and low temperature performance
- · Low foaming tendency and good seal compatibility

Applications

linelube Agri UTTO 10W-40 is suitable for use in hydraulic – transmission fluid, specifically designed for use in agricultural tractor power transmission – hydraulic systems, inboard wet brakes and rear axles, employed in the majority of modern farm tractors, agricultural machinery and some construction equipment.

Specification

- **API** GL-4
- JOHN DEERE J20C, J20A
- **MASSEY FERGUSON** M1145, M1143, M1141, M1135
- CASE MAT 3525, MS 1206, MS 1210
- NEW HOLLAND NH 420A, NH 410B
- VOLVO WB101, 97303

- FORD ESN-M2C134-D, ESN-M2C86-B
- **ZF** TE-ML 03E, 03L, 05F, 06E, 06F, 06K, 06P, 17E, 21E, 21F
- KUBOTA UDT
- ALLISON C-4
- **CATERPILLAR** TO-2
- VALTRA G2-08, G2-B10

Typical Test Data

| Specific gravity @ 15.6°C | 0.883 |
|-------------------------------|-------|
| Kinematic viscosity at 40 °C | 61.9 |
| Kinematic viscosity at 100 °C | 9.70 |
| Viscosity index | 141 |
| Pour Point | -38 |
| Flash Point | 224 |
| Total Base Number | 10.0 |
| | |

Health & Safety

For health and safety information please refer to the relevant health & safety data sheet on our website.

The contents of this data sheet are given in good faith but without warranty.

www.linelube.co.uk Last update: 13/06/2024