



## MANNOL ATF CVT 8216

A special synthetic gear oil for CVT (Continuously Variable Transmission) – variable-speed gears. It was specially developed for use in continuously variable transmissions with a rigid articulated chain or a steel pull chain. It ensures a flawless operation of an automatic gearbox, guarantees minimal wear, a lasting service life of a transmission and fuel economy.

## Product properties:

- The highest-quality unique high-viscosity synthetic base with a high viscosity index in combination with a multifunctional additive package preserves all its properties in a wide range of temperatures: it ensures good lubricating properties at low (-45 °C and lower) temperatures in winter and ensures a stable oil film under extreme loads and at high temperatures in summer:

- The high-technology combination of additives ensures superior friction properties for the chain thus ensuring a significant fuel economy, a continuous and smooth transmission shift and an extended service life of all transmission elements;

- It provides an excellent compatibility with sealing materials, prevents them from swelling, hardening and shrinking thus reducing the costs for spare parts and preventing leakages;

It has an increased thermal-oxidative and chemical stability and resistance to the high-temperature thermal degradation throughout the entire service life. It allows reducing lacquering, formation of sludge, soot and other carbon deposits, increasing the time between oil changes and ensuring the durability of transmission components thus reducing the equipment maintenance costs;
Due to the addition of special inhibitors, it effectively protects metal parts from ferrous and non-ferrous alloys from corrosion when both in and not in operation;

- It effectively resists aeration, the foam formation and cavitation, has excellent cooling properties; It has low loss by evaporation;

- It reduces noise.

The oil is a service product that requires a professional approach to selection. Its selection depends on the type of a variable-speed gear instead of the make of a vehicle. The oil has been tried and proved to be effective especially in Autotronic Mercedes-Benz Class A and B gearboxes, and in continuously variable automatic transmissions (Multitronic) in Audi vehicles. Colour: yellow-brown.

## Recommendation

VOLKSWAGEN G 052 180 VOLKSWAGEN G 052 180 BMW 83 22 0 429 154 BMW 83 22 0 429 154

BMW CVT EZL 799A BMW CVT EZL 799A CHRYSLER CVT FLUID NS-2 CHRYSLER CVT FLUID NS-2 DAIHATSU AMIX CVT FLUID DC DAIHATSU AMIX CVT FLUID DC FORD WSS M2C928-A FORD WSS M2C928-A FORD WSS M2C933-A FORD WSS M2C933-A FORD CVT FLUID 23 FORD CVT FLUID 23 FORD CVT FLUID 30 FORD CVT FLUID 30 FORD Mercon C FORD Mercon C GM DEX-CVT GM DEX-CVT HONDA HMMF (08260-99904) HONDA HMMF (08260-99904) HONDA HCF-2 HONDA HCF-2 HYUNDAI ATF SP-III HYUNDAI ATF SP-III **INFINITI** null INFINITI JEEP CVT FLUID NS-2 JEEP CVT FLUID NS-2 **KIA ATF-SP-III KIA ATF-SP-III** LEXUS null LEXUS MAZDA CVT FLUID JWS 3320 MAZDA CVT FLUID JWS 3320 MB 236.20 MB 236.20 MINI CVT EZL 799A MINI CVT EZL 799A MINI 83 22 0 429 154 MINI 83 22 0 429 154 MITSUBISHI DIAQUEEN CVT FLUID J1 MITSUBISHI DIAQUEEN CVT FLUID J1 MITSUBISHI DIAQUEEN CVT FLUID J4 MITSUBISHI DIAQUEEN CVT FLUID J4 MITSUBISHI CVT ATF SP-III MITSUBISHI CVT ATF SP-III MOPAR CVTF +4 MOPAR CVTF +4 NISSAN CVT FLUID NS-1 NISSAN CVT FLUID NS-1 NISSAN NS-2 (KLE52-00004) NISSAN NS-2 (KLE52-00004) SUBARU CVT OIL FOR LINEARTRONIC (K0425Y0710) SUBARU CVT OIL FOR LINEARTRONIC (K0425Y0710) SUBARU i-CVT FLUID SUBARU i-CVT FLUID SUBARU i-CVT FLUID FG SUBARU i-CVT FLUID FG

SUZUKI SCVT FLUID SUZUKI SCVT FLUID SUZUKI CVT OIL SUZUKI CVT FLUID GREEN 1 SUZUKI CVT FLUID GREEN 1 SUZUKI CVT FLUID GREEN 2 SUZUKI CVT FLUID GREEN 2 SUZUKI NS-2 SUZUKI NS-2 TOYOTA CVT FLUID TC TOYOTA CVT FLUID TC TOYOTA CVT FLUID FE TOYOTA CVT FLUID FE

## PACKAGING

	MN8216-1		
	MN8216-IBC		
208L	MN8216-DR	Drum	
60L	MN8216-60	Drum	
20L	MN8216-20	Plastic	
10L	MN8216-10	Plastic	
4L	MN8216-4	Plastic	4 pcs/box