

Safety data sheet according to 1907/2006/EC, Article 31

Version number 2305 (replaces version 2211)

Revision: 11.05.2023

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

- · 1.1 Product identifier
- Trade name: MANNOL 9889 M-40 Lubricant 5L
- · UFI: 50DV-N06R-C00S-XSGV
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.
- Application of the substance / the mixture Lubricant

Rust remover/ rust-removing agent

- 1.3 Details of the supplier of the safety data sheet • Manufacturer/Supplier:
- SCT-Vertriebs GmbH Feldstrasse 154 22880 WEDEL DEUTSCHLAND +49 (0)4103 1211 0 info@sct-germany.de
- Further information obtainable from: Product safety department.
- · 1.4 Emergency telephone number:

Members of the public seeking specific information on poisons should contact: In England and Wales: NHS 111 - dial 111 In Scotland: NHS 24 - dial 111

SECTION 2:	Hazards identification
	ion of the substance or mixture according to Regulation (EC) No 1272/2008
	02 flame
Flam. Liq. 3	H226 Flammable liquid and vapour.
GHSC)8 health hazard
Asp. Tox. 1	H304 May be fatal if swallowed and enters airways.
GHSC)5 corrosion
Eye Dam. 1	H318 Causes serious eye damage.
GHSC	9 environment
Aquatic Chronic	c 2 H411 Toxic to aquatic life with long lasting effects. (Contd. on page 2

IE



Printing date 11.05.2023

Safety data sheet according to 1907/2006/EC, Article 31

Version number 2305 (replaces version 2211)

Revision: 11.05.2023

Trade name: MANNOL 9889 M-40 Lubricant 5L

(Contd. of page 1) GHS07 Skin Irrit. 2 H315 Causes skin irritation. · 2.2 Label elements · Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation. · Hazard pictograms GHS02 GHS05 GHS08 GHS09 · Signal word Danger · Hazard-determining components of labelling: Dodecenvlsuccinic acid Distillates (petroleum), hydrotreated light Octadecylamine · Hazard statements H226 Flammable liquid and vapour. H315 Causes skin irritation. H318 Causes serious eye damage. H304 May be fatal if swallowed and enters airways. H411 Toxic to aquatic life with long lasting effects. Precautionary statements P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P103 Read carefully and follow all instructions. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smokina. P240 Ground and bond container and receiving equipment. Use explosion-proof [electrical/ventilating/lighting] equipment. P241 P264 Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection/hearing P280 protection. P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor. P321 Specific treatment (see on this label). P331 Do NOT induce vomiting. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P362+P364 Take off contaminated clothing and wash it before reuse. P391 Collect spillage. Store locked up. P405 Dispose of contents/container in accordance with local/regional/national/international P501 regulations. (Contd. on page 3)



Safety data sheet according to 1907/2006/EC, Article 31

Version number 2305 (replaces version 2211)

Revision: 11.05.2023

Trade name: MANNOL 9889 M-40 Lubricant 5L

(Contd. of page 2)

2.3 Other hazards

· Results of PBT and vPvB assessment

- PBT: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

Dangerous compor	nents:	
CAS: 64742-47-8	Distillates (petroleum), hydrotreated light	40–53%
EINECS: 265-149-8	Flam. Liq. 3, H226; Asp. Tox. 1, H304	
	Dodecenylsuccinic acid	5–16%
EINECS: 249-757-0	Alternative CAS number: 11059-31-7	
	Eye Dam. 1, H318; Aquatic Chronic 3, H412	
CAS: 111-76-2	2-butoxyethanol	5–11%
EINECS: 203-905-0	Acute Tox. 3, H311; Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319 ATE: LD50 oral: 1,200 mg/kg	
CAS: 124-30-1	Octadecylamine	<0.75%
EINECS: 204-695-3	STOT RE 2, H373; Asp. Tox. 1, H304; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=10); Skin Irrit. 2, H315	
 Not dangerous sub 	stances	
CAS: 67254-74-4	Naphthenic oils	10–19.3%
EC number: 614-042	2-8	
· Additional informat	ion: For the wording of the listed hazard phrases refer to section 16.	

5 1

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: A person vomiting while laying on their back should be turned onto their side.
- 4.2 Most important symptoms and effects, both acute and delayed
- Nausea
- Coughing
- Headache

Dizziness

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

(Contd. on page 4)



Printing date 11.05.2023

Version number 2305 (replaces version 2211)

Revision: 11.05.2023

Trade name: MANNOL 9889 M-40 Lubricant 5L

(Contd. of page 3)

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- **Suitable extinguishing agents:** CO2. Do not use water. Foam Fire-extinguishing powder
- Sand
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.
- · Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures
 Wear protective equipment. Keep unprotected persons away.
 Ensure adequate ventilation
 Particular danger of slipping on leaked/spilled product.
 Wear protective clothing.
 6.2 Environmental precautions:
 - Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water. • 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sand
 - Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralising agent.
 - Dispose contaminated material as waste according to section 13.
 - Ensure adequate ventilation.
 - 6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling No special precautions are necessary if used correctly. • Information about fire - and explosion protection:
- Keep ignition sources away Do not smoke.

Protect against electrostatic charges.

- 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.

(Contd. on page 5)

IE



Safety data sheet according to 1907/2006/EC, Article 31

Version number 2305 (replaces version 2211)

Revision: 11.05.2023

(Contd. of page 4)

Trade name: MANNOL 9889 M-40 Lubricant 5L

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

111-76-2 2-butoxyethanol (11.0%)

OEL Short-term value: 246 mg/m³, 50 ppm Long-term value: 98 mg/m³, 20 ppm Sk, IOELV

· Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- Appropriate engineering controls No further data; see section 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

- Respiratory protection: Not required.
- · Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles

Safety glasses

(Contd. on page 6)



Safety data sheet according to 1907/2006/EC, Article 31

Version number 2305 (replaces version 2211)

Revision: 11.05.2023

Trade name: MANNOL 9889 M-40 Lubricant 5L

(Contd. of page 5)

 9.1 Information on basic physical and chemica 	I properties
· General Information	L . L
· Colour:	Brown
· Odour:	Characteristic
Odour threshold:	Not determined.
· Melting point/freezing point:	Undetermined.
· Boiling point or initial boiling point and boiling	-
range	Undetermined.
· Flammability	Not applicable.
· Lower and upper explosion limit	Not applicable.
· Lower:	0.5 Vol % (64742-47-8 Distillates (petroleu
Lowel.	hydrotreated light)
· Upper:	
	10.6 Vol % (111-76-2 2-butoxyethanol)
· Flash point:	Not applicable. Not determined.
· Decomposition temperature:	
· pH	Not determined.
· Viscosity:	Net determined
Kinematic viscosity	Not determined.
Dynamic:	Not determined.
Solubility	
water:	Not miscible or difficult to mix.
Partition coefficient n-octanol/water (log value	
· Vapour pressure at 20 °C:	1.2 hPa (111-76-2 2-butoxyethanol)
 Density and/or relative density 	
· Density at 20 °C:	0.83 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
9.2 Other information	
· Appearance:	
· Form:	Liquid
· Important information on protection of healt	
and environment, and on safety.	
· Ignition temperature:	Product is not selfigniting.
· Explosive properties:	Not determined.
· Solvent content:	
	5 11 %
 Organic solvents: VOC (EC) 	5–11 %
· Solids content:	5–11 %
	0.5–<40 %
Change in condition	Not determined
· Evaporation rate	Not determined.
 Information with regard to physical hazard classes 	b
Explosives	Void
· Flammable gases	Void
Aerosols	Void
· Oxidising gases	Void
	Void



Printing date 11.05.2023

Version number 2305 (replaces version 2211)

Revision: 11.05.2023

Trade name: MANNOL 9889 M-40 Lubricant 5L

		(Contd. of page 6)
· Flammable liquids		
Flammable liquid and vapour.		
Flammable solids	Void	
 Self-reactive substances and mixtures 	Void	
· Pyrophoric liquids	Void	
· Pyrophoric solids	Void	
• Self-heating substances and mixtures	Void	
• Substances and mixtures, which emit		
flammable gases in contact with water	Void	
· Oxidising liquids	Void	
Oxidising solids	Void	
· Organic peroxides	Void	
· Corrosive to metals	Void	
 Desensitised explosives 	Void	

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- 10.6 Hazardous decomposition products:
- Carbon monoxide
- Aldehyde

Poisonous gases/vapours

Carbon dioxide

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

• Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

-	-	-
Oral	LD50	13,455–29,600 mg/kg (rat)
Dermal	LD50	3,636–8,000 mg/kg (rab)
Inhalative	LC50/4 h	100–220 mg/l

111-76-2 2-butoxyethanol

Oral	LD50	1,480 mg/kg (rat)
Dermal	LD50	400 mg/kg (rab)

· Skin corrosion/irritation

Causes skin irritation.

- · Serious eye damage/irritation
- Causes serious eye damage.

· **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

(Contd. on page 8)

IE -



Safety data sheet according to 1907/2006/EC, Article 31

Version number 2305 (replaces version 2211)

Revision: 11.05.2023

Trade name: MANNOL 9889 M-40 Lubricant 5L

(Contd. of page 7)

- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard
- May be fatal if swallowed and enters airways.
- 11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity

- Aquatic toxicity: No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

- 12.7 Other adverse effects
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water Do not allow product to reach ground water, water course or sewage system, even in small quantities. Must not reach sewage water or drainage ditch undiluted or unneutralised.

Danger to drinking water if even extremely small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · European waste catalogue
- HP3 Flammable

HP4 Irritant - skin irritation and eye damage

HP6 Acute Toxicity

HP14 Ecotoxic

(Contd. on page 9)



Safety data sheet according to 1907/2006/EC, Article 31

Version number 2305 (replaces version 2211)

Revision: 11.05.2023

Trade name: MANNOL 9889 M-40 Lubricant 5L

(Contd. of page 8)

· Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

14.1 UN number or ID number	
ADR, IMDG, IATA	UN1993
14.2 UN proper shipping name	
ADR	1993 FLAMMABLE LIQUID, N.O.S. (Distillat
	(petroleum), hydrotreated light, 2-butoxyethano ENVIRONMENTALLY HAZARDOUS
IMDG	FLAMMABLE LIQUID, N.O.S. (Distillates (petroleun
	hydrotreated light, Octadecylamine), MARIN
ΙΑΤΑ	POLLUTANT FLAMMABLE LIQUID, N.O.S. (Distillates (petroleun
	hydrotreated light)
14.3 Transport hazard class(es)	
ADR, IMDG	
Class	3 Flammable liquids.
Label	3
Class	3 Flammable liquids.
Label	3
14.4 Packing group	
ADR, IMDG, IATA	
14.5 Environmental hazards:	Product contains environmentally hazardous substances: Octadecylamine
Marine pollutant:	Symbol (fish and tree)
Special marking (ADR):	Symbol (fish and tree)
14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code): EMS Number:	30 F-E,S-E
Stowage Category	A
14.7 Maritime transport in bulk according to	
IMO instruments	Not applicable.



Printing date 11.05.2023

Version number 2305 (replaces version 2211)

Revision: 11.05.2023

Trade name: MANNOL 9889 M-40 Lubricant 5L

(Contd. of page s
5L
Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml
3
D/E
5L
Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml
UN 1993 FLAMMABLE LIQUID, N.O.S
(DISTILLATES (PETROLEUM), HYDROTREATE
LIGHT, 2-BUTOXYETHANOL), 3, III
ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category
- E2 Hazardous to the Aquatic Environment P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

 DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

 Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

 Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

(Contd. on page 11)

Version number 2305 (replaces version 2211)

Revision: 11.05.2023

Trade name: MANNOL 9889 M-40 Lubricant 5L

(Contd. of page 10)

- National regulations:
- Additional classification according to Decree on Hazardous Materials, Annex II: Carcinogenic hazardous material group III (dangerous).
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.

- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H311 Toxic in contact with skin.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.
- · Department issuing SDS: Product safety department.
- Date of previous version: 30.11.2022
- · Version number of previous version: 2211

· Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity - Category 4 Acute Tox. 3: Acute toxicity - Category 3 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2 Asp. Tox. 1: Aspiration hazard – Category 1 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

** Data compared to the previous version altered.



Printing date 11.05.2023