



Description

Premium class low-friction motor oil. Provides outstanding protection against wear, lowers oil and fuel consumption, keeps the engine clean and ensures fast oil penetration.

Properties

- smooth engine running
- tested for turbochargers and catalytic converters
- high lubrication reliability
- instant lubrication after cold start
- optimum stability to aging
- outstanding engine cleanliness
- high shear stability
- saves fuel and reduces pollutant emissions
- excellent wear resistance

Specifications / Approvals

JASO GLV-1

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required:

Mazda • Toyota 08880-84112 • Toyota 08880-84113

Technical data

SAE class (engine oils)	0W-8 SAE J300
Density at 15 °C	0,845 g/cm ³ DIN 51757
Viscosity at 40 °C	25,0 mm ² /s ASTM D7042
Viscosity at 100 °C	5,2 mm ² /s ASTM D7042
Viscosity at -40 °C (MRV)	< 60000 mPas ASTM D4684
Viscosity at -35 °C (CCS)	≤ 6200 mPas ASTM D5293
Viscosity index	140 DIN ISO 2909
HTHS at 150°C	≥ 1,7 mPas ASTM D5481
Pour point	-42 °C DIN ISO 3016
Flash point	230 °C DIN ISO 2592
Evaporation loss (Noack)	13,5 % CEC-L-40-A-93
Total base number	7,2 mg KOH/g DIN ISO 3771

Technical data

Sulfate ash	0,9 g/100g DIN 51575
Color number (ASTM)	L 2,5 DIN ISO 2049

Areas of application

Optimal for hybrid vehicles that require a lubricant of this specification and viscosity. Especially where there are long intervals between oil changes and high requirements on the engine.

Application

The specifications and instructions from the assembly or vehicle manufacturer must be followed. Optimum effect only when the product is used unmixed.

Available pack sizes

1 l Canister plastic	21767 AR-BG-CS-DA-DE-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH
4 l Canister plastic	21768 AR-BG-CS-DA-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH
5 l Canister plastic	21769 AR-BG-CS-DA-DE-EL-EN-ES-FI-FR-HR-HU-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-ZH
20 l Canister plastic	21770 DE-EN-ES-IT-PT
60 l Black plate barrel	21771 DE-EN-ES-FR-IT-PT
205 l Black plate barrel	21772 DE-EN-ES-FR-IT-PT

Our information is based on thorough research and may be considered reliable, although not legally binding.