



SAFETY DATA SHEET

According to HSNO Approved Code of Practice 8-1 09-06

SDS #: 085975

QUARTZ INEO FDE 0W-30

Issuing date: 2019-10-21

Revision Date: 2019-10-21

Version 1

1. IDENTIFICATION OF THE SUBSTANCE OR MIXTURE AND OF THE SUPPLIER

Product identifier

Product name QUARTZ INEO FDE 0W-30

Other means of identification

Number ERO
Substance/mixture Mixture

Recommended use of the chemical and restrictions on use

Identified uses Engine oil.

Details of the supplier of the safety data sheet

Supplier TOTAL OIL ASIA PACIFIC PTE LTD
 182 Cecil Street
 #27-01 Frasers Tower
 Singapore 069547
 Tel: +65 6879 2200
 Fax: +65 6879 2203

Importer Oil Intel Limited
 56 Whakatu Road, Whakatu
 Hastings 4172
 NEW ZEALAND
 Phone: +64 (06) 871 53 25
 Fax: +64 (06) 870 48 90

For further information, please contact:

Contact Point HSE
E-mail Address ms.ap-sds@total.com

Emergency telephone

New Zealand: +64 9 929 1483
 Asia-Pacific: +65 3158 1074
 New Zealand Poisons Information Centre: 0800 764 766

2. HAZARDS IDENTIFICATION

Classification of the substance or mixture

Not classified as hazardous according to criteria in the Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001

Version ZGHS



SDS # : 085975

QUARTZ INEO FDE 0W-30

Issuing date: 2019-10-21

Revision Date: 2019-10-21

Version 1

GHS Label elements, including precautionary statementsSignal word **None****Hazard Statements**

None

Other hazards which do not result in classification

Physical-Chemical Properties Contaminated surfaces will be extremely slippery.
Environmental properties The product may form an oil film on the water surface that may stop the oxygen exchange.

3. COMPOSITION/INFORMATION ON INGREDIENTS**Chemical nature** Mineral oil of petroleum origin.

Chemical Name	CAS-No	EC-No	Weight %
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	265-157-1	70-<80
bis(nonylphenyl)amine	36878-20-3	253-249-4	1-<2.5
C14-16-18 Alkyl phenol	^	931-468-2	1-<3

Additional information Product containing mineral oil with less than 3% DMSO extract as measured by IP 346**4. FIRST AID MEASURES****Description of necessary first-aid measures**

General advice IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR EMERGENCY MEDICAL CARE.

Eye contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing.

Skin contact Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Wash contaminated clothing before reuse.

Inhalation Remove casualty to fresh air and keep at rest in a position comfortable for breathing. If not breathing, give artificial respiration.

Ingestion Clean mouth with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or Poison Control Center immediately.

Protection of First-aiders First aider needs to protect himself. See Section 8 for more detail. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper

Version ZGHS



SDS # : 085975

QUARTZ INEO FDE 0W-30

Issuing date: 2019-10-21

Revision Date: 2019-10-21

Version 1

respiratory medical device.

Most important symptoms/effects, acute and delayed

Skin contact	Not classified based on available data. May produce an allergic reaction.
Eye contact	Not classified based on available data.
Inhalation	Not classified based on available data. Inhalation of vapors in high concentration may cause irritation of respiratory system.
Ingestion	Not classified based on available data. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Suitable Extinguishing Media Carbon dioxide (CO₂). ABC powder. Foam. Water spray or fog.

Unsuitable Extinguishing Media Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

Special Hazard Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These may be highly dangerous if inhaled in confined spaces or at high concentration. Combustion products include sulphur oxides (SO₂ and SO₃) and Hydrogen sulphide H₂S, Mercaptans, Nitrogen oxides (NO_x), Phosphorous oxides, Zinc oxides.

Advice for fire-fighters

Special protective equipment for fire-fighters Wear self-contained breathing apparatus and protective suit.

Other information

Cool containers / tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

General Information Do not touch or walk through spilled material. Contaminated surfaces will be extremely slippery. Use personal protective equipment. Ensure adequate ventilation. Remove all

Version ZGHS



SDS # : 085975

QUARTZ INEO FDE 0W-30

Issuing date: 2019-10-21

Revision Date: 2019-10-21

Version 1

sources of ignition.

Environmental precautions

General Information

Do not allow material to contaminate ground water system. Prevent entry into waterways, sewers, basements or confined areas. Local authorities should be advised if significant spillages cannot be contained.

Methods and material for containment and cleaning up

Methods for containment

Dike to collect large liquid spills. If necessary dike the product with dry earth, sand or similar non-combustible materials.

Methods for cleaning up

Dispose of contents/container in accordance with local regulation. In case of soil contamination, remove contaminated soil for remediation or disposal, in accordance with local regulations.

Other information

Personal Protective Equipment

See Section 8 for more detail.

Waste treatment

See section 13.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling

For personal protection see section 8. Use only in well-ventilated areas. Do not breathe vapors or spray mist. Avoid contact with skin, eyes and clothing.

Prevention of fire and explosion

Take precautionary measures against static discharges.

Hygiene measures

Ensure the application of strict rules of hygiene by the personnel exposed to the risk of contact with the product. When using, do not eat, drink or smoke. Wash hands before breaks and immediately after handling the product. Regular cleaning of equipment, work area and clothing is recommended. Do not use abrasives, solvents or fuels. Do not dry hands with rags that have been contaminated with product. Do not put product contaminated rags into workwear pockets.

Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions

Keep away from food, drink and animal feedingstuffs. Keep in a bonded area. Keep container tightly closed. Keep preferably in the original container. Otherwise reproduce all indication of the regulation label on the new container. Do not remove the hazard labels of the containers (even if they are empty). Design the installations in order to avoid accidental emissions of product (due to seal breakage, for example) onto hot casings or electrical contacts. Store at room temperature. Protect from moisture.

Materials to Avoid

Strong oxidizing agents.

Version ZGHS



SDS # : 085975

QUARTZ INEO FDE 0W-30

Issuing date: 2019-10-21

Revision Date: 2019-10-21

Version 1

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Control parameters****Exposure limits**

Mineral oil mist:
 USA: OSHA (PEL) TWA 5 mg/m³, NIOSH (REL) TWA 5 mg/m³, STEL 10 mg/m³, ACGIH (TLV) TWA 5 mg/m³ (highly refined).

Appropriate engineering controls**Engineering Measures**

Apply technical measures to comply with the occupational exposure limits. Ensure adequate ventilation, especially in confined areas. When working in confined spaces (tanks, containers, etc.), ensure that there is a supply of air suitable for breathing and wear the recommended equipment.

Individual protection measures, such as personal protective equipment (PPE)**Personal Protective Equipment****General Information**

Protective engineering solutions should be implemented and in use before personal protective equipment is considered. The personal protective equipment (PPE) recommendations apply to the product ITSELF. In case of mixtures or formulations, it is suggested that you contact the relevant PPE suppliers.

Respiratory protection

None under normal use conditions. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Respirator with combination filter for vapour/particulate (EN 14387): Type A/P1. Warning ! filters have a limited use duration. The use of breathing apparatus must comply strictly with the manufacturer's instructions and the regulations governing their choices and uses.

Eye Protection

If splashes are likely to occur, wear: Safety glasses with side-shields. EN 166.

Skin and body protection

Wear suitable protective clothing. Protective shoes or boots. Long sleeved clothing. Type 4/6.

Hand Protection

Hydrocarbon-proof gloves: Fluorinated rubber, Nitrile rubber. In case of prolonged contact with the product, it is recommended to wear gloves complying with EN 420 and EN 374 standards, protecting at least for 480 minutes and having a thickness of 0,38 mm at least. These values are indicative only. The level of protection is provided by the material of the glove, its technical characteristics, its resistance to the chemicals to be handled, the appropriateness of its use and its replacement frequency. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

Version ZGHS



SDS # : 085975

QUARTZ INEO FDE 0W-30

Issuing date: 2019-10-21

Revision Date: 2019-10-21

Version 1

9. PHYSICAL AND CHEMICAL PROPERTIES9.1. Information on basic physical and chemical properties

Appearance	limpid
Color	yellow
Physical State @20°C	liquid
Odor	Characteristic
Odor Threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks</u>	<u>Method</u>
pH		Not applicable	
Melting point/range		Not applicable	
Boiling point/boiling range		No information available	
Flash point	209 °C 408 °F		Cleveland Open Cup (COC) Cleveland Open Cup (COC)
Evaporation rate		No information available	
Flammability Limits in Air			
upper		No information available	
Lower		No information available	
Vapor Pressure		No information available	
Vapor density		No information available	
Relative density	0.842	@ 15 °C	
Density	842 kg/m ³	@ 15 °C	
Water solubility		Insoluble	
Solubility in other solvents		No information available	
logPow		No information available	
Autoignition temperature		No information available	
Decomposition temperature		No information available	
Viscosity, kinematic	45.91 mm ² /s	@ 40 °C	ASTM D445
Explosive properties	Not explosive		
Oxidizing Properties	Not applicable		
Possibility of hazardous reactions	None under normal processing		

9.2. Other information

Freezing Point	No information available
----------------	--------------------------

10. STABILITY AND REACTIVITY

<u>Reactivity</u>	None under normal processing.
<u>Chemical stability</u>	Stable under recommended storage conditions.

Version ZGHS



SDS # : 085975

QUARTZ INEO FDE 0W-30

Issuing date: 2019-10-21

Revision Date: 2019-10-21

Version 1

Possibility of hazardous reactions No dangerous reaction known under conditions of normal use.

Conditions to avoid Keep away from open flames, hot surfaces and sources of ignition. Keep away from heat and sparks.

Incompatible materials Strong oxidizing agents.

Hazardous Decomposition Products Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. Combustion products include sulphur oxides (SO₂ and SO₃) and Hydrogen sulphide H₂S, Mercaptans, Nitrogen oxides (NO_x), Phosphorous oxides, Zinc oxides.

11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation Not classified based on available data. Inhalation of vapors in high concentration may cause irritation of respiratory system.

Ingestion Not classified based on available data. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Skin contact Not classified based on available data. May produce an allergic reaction.

Eye contact Not classified based on available data.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure**Acute toxicity - Product Information**

Oral Not classified based on available data.
ATEmix (oral) > 5,000.00 mg/kg
 9E-06 % of the mixture consists of ingredient(s) of unknown acute oral toxicity

Dermal Not classified based on available data.
ATEmix (dermal) > 5,000.00 mg/kg
 9E-06 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity

Inhalation Not classified based on available data
ATEmix (inhalation-gas) > 20,000.00 ppm
 89.456469 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)
ATEmix (inhalation-vapor) > 20.00 mg/l
 89.456469 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)
ATEmix (inhalation-dust/mist) 5.80 mg/l
 1.217709 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

Version ZGHS



SDS # : 085975

QUARTZ INEO FDE 0W-30

Issuing date: 2019-10-21

Revision Date: 2019-10-21

Version 1

Acute toxicity - Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Distillates (petroleum), hydrotreated heavy paraffinic 64742-54-7	LD50 > 5000 mg/kg bw (rat - OECD 420)	LD50 > 5000 mg/kg bw (rabbit - OECD 402)	LC50 (4h) > 5 mg/l (aerosol) (rat - OECD 403)
bis(nonylphenyl)amine 36878-20-3	LD50 > 5000 mg/kg (Rat - OECD 401)	LD50 > 2000 mg/kg (Rat - OECD 402)	
C14-16-18 Alkyl phenol ^	LD50 2000 mg/kg bw (rat)	LD50 2000 mg/kg bw (rat)	

Skin corrosion/irritation Not classified based on available data.**Serious eye damage/eye irritation** Not classified based on available data.**Sensitization** Not classified based on available data. Contains sensitizer(s). May produce an allergic reaction. The supplier of one or more of the components contained within this formulation has indicated that he has data on the components and/or similar mixtures, which confirms that at the concentration used, classification is not required.**Carcinogenicity** Not classified based on available data. During use in engines, contamination of oil with low levels of combustion products occurs. Used motor oils have been shown to cause skin cancer in mice following repeated application and continuous exposure. Brief or intermittent skin contact with used motor oil is not expected to have serious effects in humans if the oil is thoroughly removed by washing with soap and water.**Germ Cell Mutagenicity** Not classified based on available data**Reproductive toxicity** Not classified based on available data.**Target Organ Effects (STOT)** None known**STOT - single exposure** Not classified based on available data**STOT - repeated exposure** Not classified based on available data**Aspiration hazard** Not classified based on available data.**Other adverse effects** Characteristic skin lesions (pimples) may develop following prolonged and repeated exposures (contact with contaminated clothing).**12. ECOLOGICAL INFORMATION****Ecotoxicity**

Not classified based on available data.

Acute aquatic toxicity - Product Information

Version ZGHS



SDS # : 085975

QUARTZ INEO FDE 0W-30

Issuing date: 2019-10-21

Revision Date: 2019-10-21

Version 1

No information available.

Acute aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to daphnia and other aquatic invertebrates	Toxicity to fish	Toxicity to microorganisms
Distillates (petroleum), hydrotreated heavy paraffinic 64742-54-7	EL50 (48h) > 100 mg/l (Pseudokirchnerella subcapitata - OECD 201)	EL50 (48h) > 10000 mg/l (Daphnia magna - OECD 202)	LL50 (96h) > 100 mg/l (Oncorhynchus mykiss - OECD 203)	
bis(nonylphenyl)amine 36878-20-3	EC50(72h) 600 mg/l (Selenastrum capricornutum)	EC50 (48h) > 100 mg/l (Daphnia magna - OECD 202)	LC50(96h) > 100 mg/l (Zebra Fish)	EC50(0.1 d) > 1,000 mg/l (Sludge)
C14-16-18 Alkyl phenol ^		EC50(48h) > 100 mg/l (Daphnia magna - static - OECD202)		

Chronic aquatic toxicity - Product Information

No information available.

Chronic aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to daphnia and other aquatic invertebrates	Toxicity to fish	Toxicity to microorganisms
Distillates (petroleum), hydrotreated heavy paraffinic 64742-54-7		NOEL (21d) 10 mg/l (Daphnia magna - QSAR Petrotox)	NOEL (14/28d) > 1000 mg/l (Oncorhynchus mykiss - QSAR Petrotox)	

Effects on terrestrial organisms No information available.**Persistence and degradability**

No information available.

Bioaccumulative potential**Product Information**

No information available.

logPow

No information available

Component Information

Chemical Name	log Pow
Distillates (petroleum), hydrotreated heavy paraffinic - 64742-54-7	-
bis(nonylphenyl)amine - 36878-20-3	7.7

Mobility

Version ZGHS



SDS # : 085975

QUARTZ INEO FDE 0W-30

Issuing date: 2019-10-21

Revision Date: 2019-10-21

Version 1

Soil	Given its physical and chemical characteristics, the product generally shows low soil mobility.
Air	Loss by evaporation is limited.
Water	The product is insoluble and floats on water.

Other adverse effects**General Information** No information available.**13. DISPOSAL CONSIDERATIONS**

Waste from Residues / Unused Products	Should not be released into the environment. Do not empty into drains. Dispose of in accordance with all applicable national environmental laws and regulations. Where possible recycling is preferred to disposal or incineration.
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal.
Other information	Refer to section 8 for safety and protective measures for disposal personnel.

14. TRANSPORT INFORMATION**ADR/RID** Not regulated**IMDG/IMO** Not regulated**ICAO/IATA** Not regulated**15. REGULATORY INFORMATION**

International Inventories All the substances contained in this product are listed or exempted from listing in the following inventories:
 Australia (AICS)
 Korea (KECL)
 U.S.A. (TSCA)
 Europe (EINECS/ELINCS/NLP)
 Taiwan (TCSI)
 Canada (DSL/NDSL)
 China (IECSC)
 New Zealand (NZIoC)

National regulatory information**New Zealand**

- See section 8 for national exposure control parameters
- This product is an approved substance under the Hazardous Substances and New Organisms Act (HSNO)

Version ZGHS



SDS # : 085975

QUARTZ INEO FDE 0W-30

Issuing date: 2019-10-21

Revision Date: 2019-10-21

Version 1

New Zealand HSNO approval code or group standard

HSR002605, Lubricants (Low Hazard)

This SDS may not cover all of the controls relevant for this substance or mixture. The Environmental Protection Authority of New Zealand (EPA) 'User Guide to the HSNO Controls' should be consulted for a comprehensive list of controls and reference to the regulations

16. OTHER INFORMATION

Issuing date: 2019-10-21
Revision Date: 2019-10-21
Revision Note No information available

Abbreviations, acronyms

ACGIH = American Conference of Governmental Industrial Hygienists

bw = body weight

bw/day = body weight/day

EC x = Effect Concentration associated with x% response

GLP = Good Laboratory Practice

IARC = International Agency for Research of Cancer

LC50 = 50% Lethal concentration - Concentration of a chemical in air or a chemical in water which causes the death of 50% (one half) of a group of test animals

LD50 = 50% Lethal Dose - Chemical amount, given at once, which causes the death of 50% (one half) of a group of test animals

LL = Lethal Loading

NIOSH = National Institute of Occupational Safety and Health

NOAEL = No Observed Adverse Effect Level

NOEC = No Observed Effect Concentration

NOEL = No Observed Effect Level

OECD = Organization for Economic Co-operation and Development

OSHA = Occupational Safety and Health Administration

UVCB = Substance of unknown or Variable composition, Complex reaction products or Biological material

Legend:

Section 8

Ceiling:	Maximum limit value	TWA:	Time weighted average
STEL:	Short term exposure limit	*	Skin designation
+	Sensitizer	C	Carcinogen

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.

End of the Safety Data Sheet

Version ZGHS