

Quartz 9000 Energy 0W-30

Engine oil

KEY DATA



9000

LIGHT VEHICLE RANGE

GASOLINE & DIESEL ENGINE OIL

SAE 0W-30

ADVANCED SYNTHETIC TECHNOLOGY

INTERNATIONAL STANDARDS

- ACEA A3/B4
- API SL

MANUFACTURER APPROVALS ¹

- MB-Approval 226.5
- MB-Approval 229.5
- VW 502.00/505.00
- BMW LL-01
- VOLVO VCC 95200356

¹Please refer to car owner's manual

TECHNOLOGY

Age-Resistance technology

The next gen oil for outstanding protection.

Age-Resistance technology provides expert protection, to fight everyday challenges in the long term.

Age-Resistance technology offers unbeatable engine protection. It's unique combination of hyperactive molecules creates a strong thick oil film on all concerned engine parts. Engines are absolutely protected against a variety of challenges, from wear to oil oxidation even at extreme temperatures.



APPLICATIONS

Quartz 9000 Energy 0W-30 is an advanced synthetic technology engine oil that has been developed to cover the most stringent requirements of both gasoline and diesel passengers cars engines.

Quartz 9000 Energy 0W-30 is particularly suited to the most recent engines.

This engine oil can be used in the most difficult operating conditions (motorways, city traffic...), and is appropriate for all driving types and for every season.

CUSTOMERS BENEFITS

- 💧 Anti-wear protection: this oil ensures optimum engine longevity with its anti-wear properties that protect the engine's most sensitive parts.
- 💧 Oxidation resistance: this lubricant allows extra long drain intervals.
- 💧 Engine protection, cleanliness and performance: This oil contains detergent and dispersive additives that keep the engine clean and thus preserve its power.
- 💧 Easier cold starts: Quartz 9000 Energy 0W-30 is perfectly adapted for cold starting in extreme weather conditions and ensures a good protection of mechanical parts at high temperatures as well.
- 💧 Fuel Savings: Thanks to its exceptional fluidity, this oil reduces friction and therefore creates significant fuel savings and reduces CO2 emissions.

CHARACTERISTICS²

TEST	UNIT	TEST METHOD	RESULT
Viscosity grade	-	SAE J300	0W-30
Kinematic viscosity at 40°C	mm ² /s	ASTM D445	60.9
Kinematic viscosity at 100°C	mm ² /s	ASTM D445	12.3
Density at 15°C	kg/m ³	ASTM D1298	844.4
Viscosity index	-	ASTM D2270	204
Pour point	°C	ASTM D97	-48
OC Flash point	°C	ASTM D92	242

² The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

RECOMMENDATIONS FOR USE

Before using the product, the vehicle's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations. If possible, the packaging should not be exposed to the elements. Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

HEALTH, SAFETY AND THE ENVIRONMENT

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet (SDS).

This can be obtained on request from your local reseller and is available for consultation at <https://ms-sds.totalenergies.com>.

This product should not be used for any purposes other than the ones for which it is intended.



TotalEnergies Lubricants / Last update of this datasheet: June 23 / Quartz 9000 Energy 0W-30

Some variations can be expected under normal production conditions, but these should not affect the product's expected performance irrespective of the site. The information contained in this document is subject to change without notice. Our products can be viewed on our website at www.lubricants.totalenergies.com.