



SAFETY DATA SHEET

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by
Commission Regulation (EU) 2020/878

QUARTZ INEO C1 5W-30

SDS #: 083616

previous revision date : 2022/09/19

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Product name : QUARTZ INEO C1 5W-30

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses
Engine oil

1.3 Details of the supplier of the safety data sheet

TotalEnergies Lubrifiants
562 Avenue du Parc de L'île
92029 Nanterre Cedex FRANCE
Tél: +33 (0)1 41 35 40 00
Fax: +33 (0)1 41 35 84 71
rm.msds-lubs@totalenergies.com

TotalEnergies Marketing Romania SA
Str. Stejarilor, nr. 2, Cristian,
Brasov, 507055
Tel: 00 40 268 40 17 11
Fax: 00 40 268 40 17 26
fds-romania@totalenergies.com

Contact

H.S.E

1.4 Emergency telephone number

National advisory body/Poison Center

Telephone number : Romania
Emergency Clinical Hospital Bucharest (non-stop, 24 h/7d): 021 5992300, int. 182,
444, 213, 455
Other bodies responsible for receiving health information:
Targu Mures County Emergency Clinical Hospital Direct phone: 0265 210 110
Central Telephone (non-stop, 24 h/7z): 0372 653 100; 0372 683 700; 0265 212 111
Other institutions (child poisoning): Grigore Alexandrescu Children's Hospital,
Bucharest TOXAPEL Telephone (24h/24h): 021 2106282; 021 2106183
Moldavia
Serviciul Național Unic Pentru Apelurile de Urgență: 112

Supplier

Telephone number : Emergency phone: +44 1235 239670

**SECTION 2: Hazards identification****2.1 Classification of the substance or mixture**

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Signal word : No signal word.

Hazard statements : No known significant effects or critical hazards.

Precautionary statements

Prevention : Not applicable.

Response : Not applicable.

Storage : Not applicable.

Disposal : Not applicable.

Supplemental label elements : Contains C14-16-18 Alkyl phenol. May produce an allergic reaction.
Safety data sheet available on request.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

2.3 Other hazardsThis mixture does not contain any substances that are assessed to be a PBT or a vPvB in a concentration $\geq 0,1$ %.

Other hazards which do not result in classification : Hazard of slipping on spilled product.

SECTION 3: Composition/information on ingredients**3.2 Mixtures** : Mixture

Product/substance	Identifiers	% (w/w)	Classification	Specific Conc. Limits, M-factors and ATEs	Type
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	REACH #: 01-2119474889-13 EC: 276-738-4 CAS: 72623-87-1 Index: 649-483-00-5	$\geq 75 - \leq 90$	Asp. Tox. 1, H304	-	[1] [2]
Distillates (petroleum), hydrotreated heavy paraffinic	REACH #: 01-2119484627-25 EC: 265-157-1 CAS: 64742-54-7 Index: 649-467-00-8	≤ 10	Asp. Tox. 1, H304	-	[1] [2]
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	REACH #: 01-2119474878-16 EC: 276-737-9 CAS: 72623-86-0	≤ 3	Asp. Tox. 1, H304	-	[1] [2]



Distillates (petroleum), solvent-dewaxed heavy paraffinic	Index: 649-482-00-X REACH #: 01-2119471299-27 EC: 265-169-7 CAS: 64742-65-0 Index: 649-474-00-6	≤3	Asp. Tox. 1, H304	-	[1] [2]
Distillates (petroleum), solvent-dewaxed light paraffinic	REACH #: 01-2119480132-48 EC: 265-159-2 CAS: 64742-56-9 Index: 649-469-00-9	≤3	Asp. Tox. 1, H304	-	[1] [2]
Paraffin oils (petroleum), catalytic dewaxed heavy	REACH #: 01-2119487080-42 EC: 265-174-4 CAS: 64742-70-7	≤3	Asp. Tox. 1, H304	-	[1] [2]
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	REACH #: 01-2119491299-23 EC: 270-128-1 CAS: 68411-46-1	≤0.3	Repr. 2, H361f	-	[1]
C14-16-18 Alkyl phenol	REACH #: 01-2119498288-19 EC: 931-468-2	≤0.3	Skin Sens. 1B, H317 STOT RE 2, H373	-	[1]
			See Section 16 for the full text of the H statements declared above.		

Additional information : Mineral oil of petroleum origin. Product containing mineral oil with less than 3% DMSO extract as measured by IP 346

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur.
- Skin contact** : Wash skin thoroughly with soap and water or use recognized skin cleanser. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
- Ingestion** : Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training.



4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation dryness cracking
Ingestion	: No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media	: Use dry chemical, CO ₂ , water spray (fog) or foam.
Unsuitable extinguishing media	: Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous combustion products	: carbon monoxide carbon dioxide nitrogen oxides phosphorus oxides Zinc oxides sulfur oxides Hydrogen sulfide Mercaptans

5.3 Advice for firefighters

Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.



SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

- 6.2 Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.

- 6.4 Reference to other sections** : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8).
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

- Recommendations** : Not available.
- Industrial sector specific solutions** : Not available.

**SECTION 8: Exposure controls/personal protection****8.1 Control parameters****Occupational exposure limits**

Product/substance	Exposure limit values
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	HG 1218/2006, Annex 1, with subsequent modifications and additions (Romania, 3/2021). [Mineral oil, other than mineral oils that have previously been used in internal combustion engines to lubricate and cool moving parts of the engine] VLA: 5 mg/m ³ 8 hours. Short term: 10 mg/m ³ 15 minutes.
Distillates (petroleum), hydrotreated heavy paraffinic	HG 1218/2006, Annex 1, with subsequent modifications and additions (Romania, 3/2021). [Mineral oil, other than mineral oils that have previously been used in internal combustion engines to lubricate and cool moving parts of the engine] VLA: 5 mg/m ³ 8 hours. Short term: 10 mg/m ³ 15 minutes.
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	HG 1218/2006, Annex 1, with subsequent modifications and additions (Romania, 3/2021). [Mineral oil, other than mineral oils that have previously been used in internal combustion engines to lubricate and cool moving parts of the engine] VLA: 5 mg/m ³ 8 hours. Short term: 10 mg/m ³ 15 minutes.
Distillates (petroleum), solvent-dewaxed heavy paraffinic	HG 1218/2006, Annex 1, with subsequent modifications and additions (Romania, 3/2021). [Mineral oil, other than mineral oils that have previously been used in internal combustion engines to lubricate and cool moving parts of the engine] VLA: 5 mg/m ³ 8 hours. Short term: 10 mg/m ³ 15 minutes.
Distillates (petroleum), solvent-dewaxed light paraffinic	HG 1218/2006, Annex 1, with subsequent modifications and additions (Romania, 3/2021). [Mineral oil, other than mineral oils that have previously been used in internal combustion engines to lubricate and cool moving parts of the engine] VLA: 5 mg/m ³ 8 hours. Short term: 10 mg/m ³ 15 minutes.
Paraffin oils (petroleum), catalytic dewaxed heavy	HG 1218/2006, Annex 1, with subsequent modifications and additions (Romania, 3/2021). [Mineral oil, other than mineral oils that have previously been used in internal combustion engines to lubricate and cool moving parts of the engine] VLA: 5 mg/m ³ 8 hours. Short term: 10 mg/m ³ 15 minutes.

Reportable hazardous constituent(s) contained in UVCB and/or multi-constituent substance(s) complying with the classification criteria and/or with an exposure limit (OEL)

No exposure limit value known.

Biological Limit Values (BLV)

No exposure indices known.

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following:
European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance



documents for methods for the determination of hazardous substances will also be required.

Advisory OEL : Mineral oil mist: USA: OSHA (PEL) TWA 5 mg/m³, NIOSH (REL) TWA 5 mg/m³, STEL 10 mg/m³, ACGIH (TLV) TWA 5 mg/m³ (highly refined)

DNELs/DMELs

Product/substance	Type	Exposure	Value	Population	Effects
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	DNEL	Long term Inhalation	2.73 mg/m ³	Workers	Systemic
	DNEL	Long term Oral	0.74 mg/kg bw/day	General population	Local
	DNEL	Long term Inhalation	5.58 mg/m ³	Workers	Local
	DNEL	Long term Dermal	0.97 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Oral	0.74 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.97 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	1.19 mg/m ³	General population	Local
	DNEL	Long term Inhalation	2.73 mg/m ³	Workers	Systemic
	DNEL	Long term Inhalation	5.58 mg/m ³	Workers	Local
Distillates (petroleum), hydrotreated heavy paraffinic	DNEL	Long term Oral	0.74 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.97 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	1.19 mg/m ³	General population	Local
	DNEL	Long term Inhalation	2.73 mg/m ³	Workers	Systemic
	DNEL	Long term Inhalation	5.58 mg/m ³	Workers	Local
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	DNEL	Long term Inhalation	5.4 mg/m ³	Workers	Local
	DNEL	Long term Inhalation	1.2 mg/m ³	General population	Local
	DNEL	Long term Oral	0.74 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.97 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	1.19 mg/m ³	General population	Local
	DNEL	Long term Inhalation	2.73 mg/m ³	Workers	Systemic
	DNEL	Long term Inhalation	5.58 mg/m ³	Workers	Local
	DNEL	Long term Oral	0.74 mg/kg bw/day	General population	Systemic
Distillates (petroleum), solvent-dewaxed heavy paraffinic	DNEL	Long term Dermal	0.97 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	1.19 mg/m ³	General population	Local
	DNEL	Long term Inhalation	2.73 mg/m ³	Workers	Systemic
	DNEL	Long term Inhalation	5.58 mg/m ³	Workers	Local
	DNEL	Long term Oral	0.74 mg/kg bw/day	General population	Systemic
Distillates (petroleum), solvent-	DNEL	Long term Dermal	0.97 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Oral	0.74 mg/kg bw/day	General population	Systemic



dewaxed light paraffinic	DNEL	Long term Dermal	kg bw/day 0.97 mg/	population Workers	Systemic
	DNEL	Long term Inhalation	kg bw/day 1.19 mg/m ³	General population	Local
	DNEL	Long term Inhalation	2.73 mg/m ³	Workers	Systemic
	DNEL	Long term Inhalation	5.58 mg/m ³	Workers	Local
Paraffin oils (petroleum), catalytic dewaxed heavy	DNEL	Long term Oral	0.74 mg/	General population	Systemic
	DNEL	Long term Dermal	kg bw/day 0.97 mg/	Workers	Systemic
	DNEL	Long term Inhalation	kg bw/day 1.19 mg/m ³	General population	Local
	DNEL	Long term Inhalation	2.73 mg/m ³	Workers	Systemic
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	DNEL	Long term Inhalation	5.58 mg/m ³	Workers	Local
	DNEL	Long term Oral	0.04 mg/	General population	Systemic
	DNEL	Long term Dermal	kg bw/day 0.04 mg/	General population	Systemic
	DNEL	Long term Dermal	kg bw/day 0.08 mg/	Workers	Systemic
C14-16-18 Alkyl phenol	DNEL	Long term Inhalation	kg bw/day 0.14 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	0.6 mg/m ³	Workers	Systemic
	DNEL	Long term Inhalation	1.17 mg/m ³	Workers	Systemic
	DNEL	Long term Dermal	0.3 mg/kg bw/day	Workers	Systemic

PNECs

Product/ingredient name	Compartment Detail	Name	Method Detail
Distillates (petroleum), hydrotreated heavy paraffinic	Secondary Poisoning	9.33 mg/kg	-
	Secondary Poisoning	9.33 mg/kg	-
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Fresh water	33.8 µg/l	-
	Marine water	3.38 µg/l	-
	Fresh water sediment	446 µg/kg dwt	-
	Marine water sediment	44.6 µg/kg dwt	-
	Soil	1.76 mg/kg dwt	-
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	Fresh water	0.1 mg/l	-
	Marine water	0.01 mg/l	-
	Fresh water sediment	4266.16 mg/kg dwt	-
	Marine water sediment	426.62 mg/kg dwt	-
	Soil	852.58 mg/kg dwt	-
	Sewage Treatment Plant	100 mg/l	-
	C14-16-18 Alkyl phenol		

8.2 Exposure controls

Appropriate engineering controls : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

**Individual protection measures**

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields. EN 166
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Hydrocarbon-proof gloves
nitrile rubber
Fluorinated rubber
Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.
In case of prolonged contact with the product, it is recommended to wear gloves complying with ISO 21420 and EN 374 standards, protecting at least for 480 minutes and having a thickness of 0,38 mm at least. These values are indicative only. The level of protection is provided by the material of the glove, its technical characteristics, its resistance to the chemicals to be handled, the appropriateness of its use and its replacement frequency
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : None under normal use conditions. If these are not sufficient to maintain exposure below the OEL, suitable respiratory protection must be worn (Type A/P1).
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature (20°C / 68°F) and pressure (1013 hPa) unless otherwise indicated

9.1 Information on basic physical and chemical properties**Appearance**

- Physical state** : Liquid. [limpid]
- Color** : Yellow.
- Odor** : Characteristic.
- pH** : Not applicable. Product is non-soluble (in water).
- Melting point/freezing point** : Not applicable.
- Initial boiling point and boiling range** : >316°C [ISO 3405]
- Flash point** : Open cup: 232°C [Cleveland Open Cup (COC)]
- Flammability** : Not applicable.



Lower and upper explosion limit	: Lower: 0.9% Upper: 7%
Vapor pressure	: <0.013 kPa [room temperature] Not applicable. [50°C]
Vapor density	: >2 [Air = 1]
Relative density	: 0.85 [ISO EN 3675]
Density	: 0.85 g/cm ³ [15°C] [ISO EN 3675]
Solubility(ies)	:

Media	Result
water	Not soluble

Miscible with water	: No.
Partition coefficient: n-octanol/ water	: Not applicable.
Auto-ignition temperature	: >232°C [ASTM E 659]
Decomposition temperature	: Not applicable.
Viscosity	: Kinematic (40°C): 55.2 mm ² /s [ASTM D 445]
<u>Particle characteristics</u>	
Median particle size	: Not applicable.

9.2 Other information

Pour point	: -36°C (-32.8°F)
-------------------	-------------------

SECTION 10: Stability and reactivity

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: Stable under recommended storage and handling conditions (see Section 7).
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
10.5 Incompatible materials	: <input checked="" type="checkbox"/> No specific data.
10.6 Hazardous decomposition products	: carbon monoxide carbon dioxide nitrogen oxides phosphorus oxides Zinc oxides sulfur oxides Hydrogen sulfide Mercaptans



SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/substance	Result	Species	Dose	Exposure	Test
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	LC50 Inhalation Dusts and mists	Rat	5.1 mg/l	4 hours	OECD 403
	LD50 Dermal	Rabbit - Male, Female	>5000 mg/kg	-	OECD 402
	LD50 Oral	Rat - Male, Female	>5000 mg/kg	-	Read across OECD 401
Distillates (petroleum), hydrotreated heavy paraffinic	LC50 Inhalation Dusts and mists	Rat - Male, Female	>5 mg/l	4 hours	Read across OECD 403
	LD50 Dermal	Rabbit - Male, Female	>5000 mg/kg	-	Read across OECD 402
	LD50 Oral	Rat - Male, Female	>5000 mg/kg	-	Read across OECD 401
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	LC50 Inhalation Dusts and mists	Rat	5.53 mg/l	4 hours	Read across OECD 403
	LD50 Dermal	Rabbit	>5000 mg/kg	-	OECD 402
	LD50 Oral	Rat	>5000 mg/kg	-	OECD 401
Distillates (petroleum), solvent-dewaxed heavy paraffinic	LC50 Inhalation Dusts and mists	Rat	>5 mg/l	4 hours	OECD 403
	LD50 Dermal	Rabbit	>5000 mg/kg	-	OECD 402
	LD50 Oral	Rat	>5000 mg/kg	-	OECD 420
Distillates (petroleum), solvent-dewaxed light paraffinic	LC50 Inhalation Dusts and mists	Rat	>5 mg/l	4 hours	OECD 403
	LD50 Dermal	Rabbit	>5000 mg/kg	-	OECD 402
	LD50 Oral	Rat	>5000 mg/kg	-	OECD 401
Paraffin oils (petroleum), catalytic dewaxed heavy	LC50 Inhalation Dusts and mists	Rat	5.1 mg/l	4 hours	-
	LC50 Inhalation Vapor	Rat	80.4 mg/l	1 hours	-
	LC50 Inhalation Vapor	Rat	20.1 mg/l	4 hours	-
	LD50 Dermal	Rabbit	>5000 mg/kg	-	-
	LD50 Oral	Rat	>5000 mg/kg	-	-
	LD50 Oral	Rat	>2500 mg/kg	-	-
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene C14-16-18 Alkyl phenol	LD50 Dermal	Rat	2000 mg/kg	-	-
	LD50 Oral	Rat	2000 mg/kg	-	-

Acute toxicity estimates

Product/substance	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	N/A	N/A	N/A	N/A	5.1
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	N/A	N/A	N/A	N/A	5.53
Paraffin oils (petroleum), catalytic dewaxed heavy	N/A	N/A	N/A	20.1	5.1

Conclusion/Summary : Based on available data, the classification criteria are not met.

Irritation/Corrosion

**Conclusion/Summary**

- Skin** : Based on available data, the classification criteria are not met.
Eyes : Based on available data, the classification criteria are not met.
Respiratory : Based on available data, the classification criteria are not met.

Sensitization**Conclusion/Summary**

- Skin** : Based on available data, the classification criteria are not met. Contains sensitizer. May produce an allergic reaction.
Respiratory : Based on available data, the classification criteria are not met.

Mutagenicity

- Conclusion/Summary** : Based on available data, the classification criteria are not met.

Carcinogenicity

- Conclusion/Summary** : Based on available data, the classification criteria are not met.

Reproductive toxicity

- Conclusion/Summary** : Based on available data, the classification criteria are not met.

Teratogenicity

- Conclusion/Summary** : Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

- Conclusion/Summary** : Based on available data, the classification criteria are not met.

Specific target organ toxicity (repeated exposure)

Product/substance	Category	Route of exposure	Target organs
C14-16-18 Alkyl phenol	Category 2	-	-

- Conclusion/Summary** : Based on available data, the classification criteria are not met.

Aspiration hazard

Product/substance	Result
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	ASPIRATION HAZARD - Category 1
Distillates (petroleum), hydrotreated heavy paraffinic	ASPIRATION HAZARD - Category 1
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	ASPIRATION HAZARD - Category 1
Distillates (petroleum), solvent-dewaxed heavy paraffinic	ASPIRATION HAZARD - Category 1
Distillates (petroleum), solvent-dewaxed light paraffinic	ASPIRATION HAZARD - Category 1
Paraffin oils (petroleum), catalytic dewaxed heavy	ASPIRATION HAZARD - Category 1

- Conclusion/Summary** : Based on available data, the classification criteria are not met.

- Information on the likely routes of exposure** : Not available.

Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
Inhalation : No known significant effects or critical hazards.
Skin contact : Defatting to the skin. May cause skin dryness and irritation.
Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : No specific data.
Inhalation : No specific data.



Skin contact	: Adverse symptoms may include the following: irritation dryness cracking
Ingestion	: No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure**Short term exposure**

Potential immediate effects	: Not available.
Potential delayed effects	: Not available.

Long term exposure

Potential immediate effects	: Not available.
Potential delayed effects	: Not available.

Potential chronic health effects

Not available.

Conclusion/Summary	: Not available.
General	: No known significant effects or critical hazards.
Carcinogenicity	: <input checked="" type="checkbox"/> No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.

11.2 Information on other hazards**11.2.1 Endocrine disrupting properties**

This product does not contain any substance present at a concentration equal to or greater than 0.1% by mass, included in the list drawn up in accordance with article 59, paragraph 1 of the REACH Regulation, due to its endocrine disrupting properties, or a substance known to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation 2018/605.

11.2.2 Other information Not available.**SECTION 12: Ecological information****12.1 Toxicity**

Product/substance	Result	Species	Exposure	Test
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	Acute EL50 >100 mg/l	Algae - <i>Pseudokirchneriella subcapitata</i>	48 hours	OECD 201
	Acute EL50 >10000 mg/l	Crustaceans - <i>Daphnia magna</i>	48 hours	OECD 202
	Acute LL50 >100 mg/l	Fish - <i>Pimephales promelas</i>	96 hours	OECD 203
	Chronic NOEL >100 mg/l	Algae - <i>Pseudokirchneriella subcapitata</i>	72 hours	OECD 201
	Chronic NOEL >1000 mg/l	Crustaceans - <i>Daphnia magna</i>	21 days	OECD 211
Distillates (petroleum), hydrotreated heavy paraffinic	Acute EC50 >100 mg/l	Algae - <i>Pseudokirchneriella subcapitata</i>	72 hours	OECD 201
	Acute EC50 >10000 mg/l	Crustaceans - <i>Daphnia magna</i>	48 hours	OECD 202



Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	Chronic NOEL >100 mg/l	Algae - <i>Pseudokirchneriella subcapitata</i>	72 hours	OECD 201
	Chronic NOEL >1000 mg/l	Crustaceans - <i>Daphnia magna</i>	21 days	-
	Acute EL50 >100 mg/l	Algae - <i>Pseudokirchneriella subcapitata</i>	72 hours	OECD 201
	Acute EL50 >10000 mg/l	Crustaceans - <i>Daphnia magna</i>	48 hours	OECD 202
	Acute LL50 >1000 mg/l	Fish - <i>Pimephales promelas</i>	96 hours	OECD 203
	Chronic NOEL >100 mg/l	Algae - <i>Pseudokirchneriella subcapitata</i>	72 hours	OECD 201
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Chronic NOEL >1000 mg/l	Crustaceans - <i>Daphnia magna</i>	21 days	OECD 211
	Acute EL50 >10000 mg/l	Crustaceans - <i>Daphnia magna</i>	48 hours	OECD 202
	Acute LL50 >1000 mg/l	Fish - <i>Oncorhynchus mykiss</i>	96 hours	OECD 203
	Chronic NOEL >1000 mg/l	Crustaceans - <i>Daphnia magna</i>	21 days	OECD 211
Distillates (petroleum), solvent-dewaxed light paraffinic	Acute EL50 >100 mg/l	Algae - <i>Pseudokirchneriella subcapitata</i>	72 hours	OECD 201
	Acute EL50 10000 mg/l	Crustaceans - <i>Daphnia magna</i>	48 hours	OECD 202
	Acute EL50 ≥100 mg/l	Fish - <i>Pimephales promelas</i>	96 hours	OECD 203
	Chronic NOEL >100 mg/l	Algae - <i>Pseudokirchneriella subcapitata</i>	72 hours	OECD 201
	Chronic NOEL >1000 mg/l	Crustaceans - <i>Daphnia magna</i>	21 days	OECD 211
Paraffin oils (petroleum), catalytic dewaxed heavy	Acute EC50 10000 mg/l	Daphnia	48 hours	-
	Acute NOEL 101 mg/l	Algae - <i>Pseudokirchneriella subcapitata</i>	72 hours	-
C14-16-18 Alkyl phenol	Acute EC50 >100 mg/l	Daphnia - <i>Daphnia magna</i>	48 hours	OECD 202

Conclusion/Summary : Not available.

12.2 Persistence and degradability

Product/substance	Test	Result	Dose	Inoculum
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	OECD 301F	31 % - Not readily - 28 days	-	Activated sludge
Distillates (petroleum), hydrotreated heavy paraffinic	OECD 301F	31 % - Not readily - 28 days	-	Activated sludge
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	OECD 301F	31 % - Not readily - 28 days	-	Activated sludge
Distillates (petroleum), solvent-dewaxed heavy paraffinic	OECD 301F	31 % - Not readily - 28 days	-	Activated sludge
Distillates (petroleum), solvent-dewaxed light	OECD 301F	31 % - Not readily - 28 days	-	Activated sludge



paraffinic				
------------	--	--	--	--

Conclusion/Summary : Not available.

Product/substance	Aquatic half-life	Photolysis	Biodegradability
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	-	-	Not readily
Distillates (petroleum), hydrotreated heavy paraffinic	-	-	Not readily
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	-	-	Not readily
Distillates (petroleum), solvent-dewaxed heavy paraffinic	-	-	Not readily
Distillates (petroleum), solvent-dewaxed light paraffinic	-	-	Not readily
Paraffin oils (petroleum), catalytic dewaxed heavy	-	-	Not readily
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	-	-	Not readily

12.3 Bioaccumulative potential

Product/substance	LogK _{ow}	BCF	Potential
Distillates (petroleum), hydrotreated heavy paraffinic	>4	-	High
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	6.1	-	High
Distillates (petroleum), solvent-dewaxed heavy paraffinic	9.2	260	Low
Distillates (petroleum), solvent-dewaxed light paraffinic	3.1	-	Low
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	5.1	1730	High

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Mobility : Not available.

Mobility in soil : Given its physical and chemical characteristics, the product generally shows low soil mobility. The product is insoluble and floats on water. Loss by evaporation is limited.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB in a concentration $\geq 0,1$ %.

12.6 Endocrine disrupting properties



This product does not contain any substance present at a concentration equal to or greater than 0.1% by mass, included in the list drawn up in accordance with article 59, paragraph 1 of the REACH Regulation, due to its endocrine disrupting properties, or a substance known to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation 2018/605.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : Yes.
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user based on the application for which the product was used. The following Waste Codes are only suggestions: 13 02 05*

Packaging

Methods of disposal : The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Special precautions : This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	ICAO/IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.



14.7 Maritime transport in bulk according to IMO instruments : Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorization

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Other EU regulations

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Industrial emissions (integrated pollution prevention and control) - Air : Not listed

Industrial emissions (integrated pollution prevention and control) - Water : Not listed

Explosive precursors : Not applicable.

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

National regulations

National regulatory information

GD 398/2010 on establishing measures for application of Regulation (EC) no. 1.272 / 2008 of the European Parliament and of the Council of 16 December 2008 on classification, labeling and packaging of substances and mixtures, amending and repealing Directives 67/548 / EEC and 1999/45 / EC, and amending Regulation (EC). 1.907 / 2006GD 477/2009 on establishing penalties for infringements of the provisions of Regulation (EC) no. 1.907 / 2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Agency for Chemicals, amending Directive 1999/45 / EC and repealing Regulation (EEC) No . 793/93 and Regulation (EC) no. 1,488 / 94 Commission and Council Directive 76/769 / EEC and Directives 91/155 / EEC, 93/67 / EEC, 93/105 / EC and 2000/21 / EC of the



CommissionGD 1218/2006 laying down minimum requirements for safety and health at work for the protection of workers from risks related to chemical agents

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

LU - Luxembourg prohibited chemicals in the workplace

Not listed.

Inventory list

Australia inventory (AIC)

: All components are listed or exempted.

Canada inventory (DSL/NDSL)

: All components are listed or exempted.

China inventory (IECSC)

: All components are listed or exempted.

Europe inventory (EC)

: All components are listed or exempted.

Japan inventory

: **Japan inventory (CSCL)**: All components are listed or exempted.

Japan inventory (ISHL): All components are listed or exempted.

New Zealand Inventory of Chemicals (NZIoC)

: All components are listed or exempted.

Philippines inventory (PICCS)

: All components are listed or exempted.

Korea inventory (KECI)

: All components are listed or exempted.

Taiwan Chemical Substances Inventory (TCSI)

: All components are listed or exempted.

Thailand inventory

: Not determined.

Turkey inventory

: Not determined.

United States inventory (TSCA 8b)

: All components are listed or exempted.

Vietnam inventory

: Not determined.

The information stated in this section relates solely to the conformity of the chemical product with the countries Inventories. The information used to confirm the inventory status of this product may be based on additional data to the chemical composition shown in Section 3. Other regulations may apply for importation or marketing authorizations.

15.2 Chemical Safety Assessment

: This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

**Abbreviations and acronyms**

: ATE = Acute Toxicity Estimate
 CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
 DNEL = Derived No Effect Level
 DMEL = Derived Minimal Effect Level
 EUH statement = CLP-specific Hazard statement
 N/A = Not available
 PBT = Persistent, Bioaccumulative and Toxic
 vPvB = Very Persistent and Very Bioaccumulative
 PNEC = Predicted No Effect Concentration
 LC50 = Median lethal concentration
 LD50 = Median lethal dose
 OEL = Occupational Exposure Limit
 VOC = Volatile Organic Compound
 UVCB Substance of unknown or Variable composition, Complex reaction products or Biological material
 NOEC No Observed Effect Concentration
 QSAR = Quantitative Structure–Activity Relationship

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Not classified.	

Full text of abbreviated H statements

H304 H317 H361f H373	May be fatal if swallowed and enters airways. May cause an allergic skin reaction. Suspected of damaging fertility. May cause damage to organs through prolonged or repeated exposure.
-------------------------------	---

Full text of classifications [CLP/GHS]

Asp. Tox. 1 Repr. 2 Skin Sens. 1B STOT RE 2	ASPIRATION HAZARD - Category 1 TOXIC TO REPRODUCTION - Category 2 SKIN SENSITIZATION - Category 1B SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
--	---

Date of revision : 2023/08/01

previous revision date : 2022/09/19

Version : 2.01

Notice to reader



TotalEnergies

QUARTZ INEO C1 5W-30

SDS # : 083616

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.