

Quartz Ineo ECOB 5W-20

Engine oil

KEY DATA



LIGHT VEHICLE RANGE

GASOLINE & DIESEL ENGINE OIL
SAE 5W-20
ADVANCED SYNTHETIC TECHNOLOGY
LOW SAPS & FUEL ECONOMY

INTERNATIONAL STANDARDS

- ACEA C5
- API SN
- ILSAC GF-5

MANUFACTURER APPROVALS ¹

- FORD WSS-M2C948-B
- JAGUAR LAND ROVER : STJLR.03.5004

¹ Please refer to car owner's manual

TECHNOLOGY

Age-Resistance technology

The next gen oil for outstanding protection.

Age-Resistance technology provides expert protection, to fight everyday challenges in the long term.

Age-Resistance technology offers unbeatable engine protection. It's unique combination of hyperactive molecules creates a strong thick oil film on all concerned engine parts. Engines are absolutely protected against a variety of challenges, from wear to oil oxidation even at extreme temperatures.



APPLICATIONS

Quartz Ineo ECOB 5W-20 is an advanced synthetic technology engine oil that provides the best protection against wear and deposits.

The post-treatment systems for GASOLINE engines, which are sensitive to the lubricants used and expensive to maintain, are also protected over the longterm thanks to the product's low phosphorus content.

Its 5W-20 grade reduces internal friction within the engine as much as possible so that it can deliver full power, while at the same time generating fuel savings.

Quartz Ineo ECOB 5W-20 with specification Ford WSS-M2C-948-B is particularly well-suited for use with Ford's GASOLINE powered engines (except the Ford Ka, Focus ST and Focus RS). This oil is required for the 1.0L 3 cylinder EcoBoost engines.

Quartz Ineo ECOB 5W-20 is advised for use in Jaguar Land Rover vehicles that require Jaguar Land Rover oil approval STJLR.03.5004.

CUSTOMERS BENEFITS

- Reduced environmental impact: 3,55% reduction in fuel consumption, as measured by the official ACEA M111-FE test.
- Protection for pollution-control systems: With its low phosphorus content, this lubricant also optimises the way in which three-way catalytic converters operate, preventing them from getting damaged through poisoning. This reduces NO_x, HC and CO in particular.
- Engine protection and cleanliness: This oil contains detergent and dispersive additives and offers the best possible protection in its category against wear and deposits.
- Easier cold starts: Easy cold starts due to its extreme fluidity at low temperature.
- Oil change intervals: To be modified based on the usage, please always refer to the car owner's manual.

CHARACTERISTICS²

TEST	UNIT	TEST METHOD	RESULT
Viscosity grade	-	SAE J300	5W-20
Kinematic viscosity at 40°C	mm ² /s	ASTM D445	44
Kinematic viscosity at 100°C	mm ² /s	ASTM D445	8.2
Density at 15°C	kg/m ³	ASTM D4052	851
Viscosity index	-	ASTM D2270	161
Pour point	°C	ASTM D97	-33
OC Flash point	°C	NF EN ISO 2592*	187

²The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

RECOMMENDATIONS FOR USE

Before using the product, the vehicle's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations. If possible, the packaging should not be exposed to the elements. Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

HEALTH, SAFETY AND THE ENVIRONMENT

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet (SDS).

This can be obtained on request from your local reseller and is available for consultation at <https://ms-sds.totalenergies.com>.

This product should not be used for any purposes other than the ones for which it is intended.

