

TRAXIUM AXLE 8 80W-90

Transmission Oil

KEY DATA



INTERNATIONAL STANDARDS

🔥 API GL-5 (LS)

MANUFACTURER APPROVALS

🔥 PSA PEUGEOT CITROEN B71 2375

TECHNOLOGY

Savings technology

Reduce your maintenance costs.

With Savings technology you will contribute over time to reduce your maintenance costs as your vehicle will run with fewer interruptions.

Our products offer a robust and consistent protection of your parts in all conditions, by offering performances that meet your needs in terms of reliability. Our oils are formulated to comply on multiples application using different materials and operating under different conditions due to the protective film that is applied to the parts with powerful and long-lasting properties.



APPLICATIONS

TRAXIUM AXLE 8 80W-90 is an oil specially designed for the lubrication of axles equipped with limited slip differentials, some classical axles and transfer gear boxes.

TRAXIUM AXLE 8 80W-90 is suitable for use in all passenger cars and light commercial vehicles when the manufacturer requires an oil with specific friction properties.

TRAXIUM AXLE 8 80W-90 is recommended by PSA for use in CITROËN and PEUGEOT 4 wheel drive cars and vans equipped with transfer gear boxes or axles. Also suitable for PSA synchronizers used in severe conditions (competition rally).

PERFORMANCES & CUSTOMER BENEFITS

- 🔥 Reduced cost of maintenance: specially formulated to reach the drain intervals recommended by the manufacturer.
- 🔥 Improved protection of axles against wear and corrosion due to extreme-pressure properties of oil.
- 🔥 Improved driver start up experience: low temperature fluidity due to a high viscosity index, generating benefits during cold starts and limiting drag losses and fuel consumption.
- 🔥 Improved stability in operation due to high viscosity index.
- 🔥 High compatibility with oil filters due to antifoam properties.
- 🔥 Specifically designed for vehicles with 4WD.

CHARACTERISTICS *

TEST	UNIT	TEST METHOD	RESULT
Viscosity grade	-	-	80W-90
Density at 15°C	kg/m3	ISO 3675	896
Kinematic viscosity at 40°C	mm ² /s	ISO 3104	138
Kinematic viscosity at 100°C	mm ² /s	ISO 3104	18
Viscosity index	-	ISO 2909	145
Pour point	°C	ISO 3016	-33
Flash Point	°C	ISO 2592	218

* The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

RECOMMENDATIONS FOR USE

Before using the product, the vehicle's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations. If possible, the packaging should not be exposed to the elements. Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

HEALTH, SAFETY AND THE ENVIRONMENT

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet (SDS).

This can be obtained on request from your local reseller and is available for consultation at <https://ms-sds.totalenergies.com>.

This product should not be used for any purposes other than the ones for which it is intended.

