

SAFETY DATA SHEET

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878

TRAXIUM GEAR 8 75W-80

SDS #: 090525

previous revision date

: 2023/08/03

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Product name	: TRAXIUM GEAR 8 75W-80
UFI	: Q14X-68DJ-100Y-08SQ

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Transmission fluids

1.3 Details of the supplier of the safety data sheet

TotalEnergies Lubrifiants 562 Avenue du Parc de L'ile 92029 Nanterre Cedex FRANCE Tél: +33 (0)1 41 35 40 00 Fax: +33 (0)1 41 35 84 71

rm.msds-lubs@totalenergies.com

TotalEnergies Marketing Romania SA Str. Stejarilor, nr. 2, Cristian, Brasov, 507055 Tel: 00 40 268 40 17 11 Fax: 00 40 268 40 17 26

fds-romania@totalenergies.com

Contact

H.S.E

1.4 Emergency telephone number

National advisory body/Poison Center

Telephone number	: Romania Emergency Clinical Hospital Bucharest (non-stop, 24 h/7d): 021 5992300, int. 182, 444, 213, 455 Other bodies responsible for receiving health information: Targu Mures County Emergency Clinical Hospital Direct phone: 0265 210 110 Central Telephone (non-stop, 24 h/7z): 0372 653 100; 0372 683 700; 0265 212 111 Other institutions (child poisoning): Grigore Alexandrescu Children's Hospital, Bucharest TOXAPEL Telephone (24h/24h): 021 2106282; 021 2106183 Moldavia Serviciul Național Unic Pentru Apelurile de Urgență: 112
<u>Supplier</u>	
Telephone number	: Emergency phone: +44 1235 239670



SDS #: 090525

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Eye Irrit. 2, H319

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended. See Section 16 for the full text of the H statements declared above. See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms



Signal word	: Warning
Hazard statements	: H319 - Causes serious eye irritation.
Precautionary statements	
General	 P101 - If medical advice is needed, have product container or label at hand. P102 - Keep out of reach of children. P103 - Read carefully and follow all instructions.
Prevention	: P280 - Wear eye or face protection.
Response	 P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337 + P313 - If eye irritation persists: Get medical advice or attention.
Storage	: Not applicable.
Disposal	: Not applicable.
Supplemental label elements	: Not applicable.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.

2.3 Other hazards

This mixture does not contain any substances that are assessed to be a PBT or a vPvB in a concentration >= 0,1 %. This product does not contain any substance present at a concentration equal to or greater than 0.1% by mass, included in the list drawn up in accordance with article 59, paragraph 1 of the REACh Regulation, due to its endocrine disrupting properties, or a substance known to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation 2018/605.

Other hazards which do not result in classification

: Hazard of slipping on spilled product.



SDS #: 090525

SECTION 3: Composition/information on ingredients

3.2 Mixtures	: Mixture				
Product/substance	Identifiers	% (w/w)	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
Polysulfides, di-tert-Bu	REACH #: 01-2119540515-43 EC: 273-103-3 CAS: 68937-96-2	<4.6	Skin Sens. 1B, H317 Aquatic Chronic 3, H412	Skin Sens. 1B, H317: C ≥ 46%	[1]
Distillates (petroleum), hydrotreated heavy paraffinic	REACH #: 01-2119484627-25 EC: 265-157-1 CAS: 64742-54-7 Index: 649-467-00-8	≤3	Asp. Tox. 1, H304	-	[1] [2]
zinc O,O,O',O'-tetrakis (1,3-dimethylbutyl) bis (phosphorodithioate)	REACH #: 01-2119953275-34 EC: 218-679-9 CAS: 2215-35-2	≤2	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 2, H411	Skin Irrit. 2, H315: C ≥ 10% Eye Dam. 1, H318: C ≥ 10% Eye Irrit. 2, H319: 1% ≤ C < 10%	[1]
Distillates (petroleum), hydrotreated light paraffinic	REACH #: 01-2119487077-29 EC: 265-158-7 CAS: 64742-55-8	≤3	Asp. Tox. 1, H304	-	[1] [2]
oleic acid, compound with (Z)-N-octadec- 9-enylpropane-1,3-diamine (2:1)	REACH #: 01-2119974119-29 EC: 251-846-4 CAS: 34140-91-5	≤0.3	Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 2, H411	M [Acute] = 10	[1]
			See Section 16 for the full text of the H statements declared above.		

Additional information

: Mineral oil of petroleum origin. Product containing mineral oil with less than 3% DMSO extract as measured by IP 346

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

<u>Туре</u>

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.



SECTION 4: First aid measures

4.1 Description of first aid measures Eye contact Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Oct medical attention

	minutes. Get medical attention.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Wash skin thoroughly with soap and water or use recognized skin cleanser. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation dryness cracking
Ingestion	: No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media	
Suitable extinguishing media	: Use dry chemical, CO ₂ , water spray (fog) or foam.
Unsuitable extinguishing media	: Do not use water jet.

5.2 Special hazards arising from the substance or mixture



SDS # :

090525

Hazards from the substance or mixture	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous combustion products	: Farbon monoxide carbon dioxide Silicon Dioxide nitrogen oxides phosphorus oxides Sodium oxides sulfur oxides Hydrogen sulfide Mercaptans Zinc oxides
5.3 Advice for firefighters	
Special protective actions for fire-fighters	 Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

···· · · · · · · · · · · · · · · · · ·		······································
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
6.3 Methods and materials for	r c	ontainment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.
6.4 Reference to other sections	:	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.



SDS # : 090525

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Protective measures	 Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

Recommendations	: Not available.
Industrial sector specific	: Not available.
solutions	

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

Product/substance	Exposure limit values
Distillates (petroleum), hydrotreated heavy paraffinic	HG 1218/2006, Annex 1, with subsequent modifications and additions (Romania, 3/2021). [Mineral oil, other than mineral oils that have previously been used in internal combustion engines to lubricate and cool moving parts of the engine] VLA: 5 mg/m ³ 8 hours. Short term: 10 mg/m ³ 15 minutes.
Distillates (petroleum), hydrotreated light paraffinic	HG 1218/2006, Annex 1, with subsequent modifications and additions (Romania, 3/2021). [Mineral oil, other than mineral oils that have previously been used in internal combustion engines to lubricate and cool moving parts of the engine] VLA: 5 mg/m ³ 8 hours. Short term: 10 mg/m ³ 15 minutes.

Reportable hazardous constituent(s) contained in UVCB and/or multi-constituent substance(s) complying with the classification criteria and/or with an exposure limit (OEL)

No exposure limit value known.

Biological Limit Values (BLV)

No exposure indices known.



Recommended monitoring procedures	: Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
Advisory OEL	: Mineral oil mist: USA: OSHA (PEL) TWA 5 mg/m3, NIOSH (REL) TWA 5 mg/m3, STEL 10 mg/m3, ACGIH (TLV) TWA 5 mg/m3 (highly refined)

DNELs/DMELs

Product/substance	Туре	Exposure	Value	Population	Effects
Polysulfides, di-tert-Bu	DNEL	Long term	0.58 mg/m ³	General	Systemic
		Inhalation		population	
	DNEL	Long term	3.29 mg/m ³	Workers	Systemic
		Inhalation			
	DNEL	Long term Oral	0.167 mg/	General	Systemic
		-	kg bw/day	population	-
	DNEL	Long term Dermal	1.67 mg/	General	Systemic
			kg bw/day	population	
	DNEL	Long term Dermal	4.67 mg/	Workers	Systemic
			kg bw/day		
Distillates (petroleum), hydrotreated	DNEL	Long term Oral	0.74 mg/	General	Systemic
neavy paraffinic			kg bw/day	population	
	DNEL	Long term Dermal	0.97 mg/	Workers	Systemic
			kg bw/day		
	DNEL	Long term	1.19 mg/m ³	General	Local
		Inhalation		population	
	DNEL	Long term	2.73 mg/m ³	Workers	Systemic
		Inhalation			
	DNEL	Long term	5.58 mg/m ³	Workers	Local
		Inhalation			
zinc O,O,O',O'-tetrakis	DNEL	Long term Oral	0.24 mg/	General	Systemic
(1,3-dimethylbutyl) bis			kg bw/day	population	
(phosphorodithioate)					
	DNEL	Long term	2.13 mg/m ³	General	Systemic
		Inhalation		population	
	DNEL	Long term Dermal	6.1 mg/kg	General	Systemic
			bw/day	population	
	DNEL	Long term	8.6 mg/m ³	Workers	Systemic
		Inhalation			
	DNEL	Long term Dermal	12.2 mg/	Workers	Systemic
			kg bw/day		
Distillates (petroleum), hydrotreated	DNEL	Long term Oral	0.74 mg/	General	Systemic
ight paraffinic			kg bw/day	population	
	DNEL	Long term Dermal	0.97 mg/	Workers	Systemic
			kg bw/day		
	DNEL	Long term	1.19 mg/m ³	General	Local
		Inhalation		population	
	DNEL	Long term	2.73 mg/m ³	Workers	Systemic
		Inhalation			
	DNEL	Long term	5.58 mg/m ³	Workers	Local
		Inhalation			
oleic acid, compound with (Z)-N-	DNEL	Long term Oral	5 µg/kg bw/	General	Systemic
octadec-9-enylpropane-1,3-diamine			day	population	
(2:1)					
	DNEL	Long term Dermal	5 µg/kg bw/	General	Systemic



DNEL	Long term Dermal	day 14 µg/kg bw/day	population Workers	Systemic
DNEL	Long term Inhalation	,	General population	Systemic
DNEL	Long term Inhalation	98.4 µg/m³	Workers	Systemic

PNECs

Product/ingredient name	Compartment Detail	Name	Method Detail
Polysulfides, di-tert-Bu	Fresh water	0.00024 mg/l	-
	Marine water	0.000024 mg/l	-
	Fresh water sediment	0.94 mg/kg dwt	-
	Marine water sediment	0.094 mg/kg dwt	-
	Soil	1513 mg/kg	-
	Sewage Treatment Plant	4.51 mg/l	-
Distillates (petroleum), hydrotreated heavy paraffinic	Secondary Poisoning	9.33 mg/kg	-
zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl) bis (phosphorodithioate)	Fresh water	0.004 mg/l	-
	Marine water	0.0046 mg/l	-
	Fresh water sediment	0.06 mg/kg dwt	-
	Marine water sediment	0.006 mg/kg dwt	-
	Soil	0.01 mg/kg dwt	-
	Sewage Treatment Plant	100 mg/l	-
oleic acid, compound with (Z)-N-octadec- 9-enylpropane-1,3-diamine (2:1)	Fresh water	0.00646 mg/l	-
	Marine water	0.000646 mg/l	-
	Fresh water sediment	204 mg/kg dwt	-
	Marine water sediment	20.4 mg/kg dwt	-
	Soil	9.93 mg/kg dwt	-
	Sewage Treatment Plant	99.3 mg/l	-

8.2 Exposure controls

 Appropriate engineering controls
 : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: 🖻 afety glasses with side-shields, EN 166.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.



SDS # : 090525

	 Hydrocarbon-proof gloves nitrile rubber Fluorinated rubber Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. In case of prolonged contact with the product, it is recommended to wear gloves complying with ISO 21420 and EN 374 standards, protecting at least for 480 minutes and having a thickness of 0,38 mm at least. These values are indicative only. The level of protection is provided by the material of the glove, its technical characteristics, its resistance to the chemicals to be handled, the appropriateness of its use and its replacement frequency
Body protection	: ₩ear work clothing with long sleeves. Non-skid safety shoes or boots
Respiratory protection	: Ensure adequate ventilation and check that a safe, breathable atmosphere is present before entry into confined spaces. In case of inadequate ventilation wear respiratory protection: Type A/P1. Warning ! filters have a limited use duration. The use of breathing apparatus must comply strictly with the manufacturer's instructions and the regulations governing their choices and uses.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature (20°C / 68°F) and pressure (1013 hPa) unless otherwise indicated

9.1 Information on basic physical and chemical properties

<u>Appearance</u>		
Physical state	Liquid. [limpid]	
Color	Colorless to light yellow.	
Odor	Characteristic.	
рН	Not applicable. Product is non-soluble (in water).	
Melting point/freezing point	Technically not possible to measure	
Initial boiling point and boiling range	>316°C [ISO 3405]	
Flash point	Open cup: 210°C [Cleveland Open Cup (COC)]	
Flammability	Non-flammable.	
Lower and upper explosion limit	Lower: 0.9% Upper: 7%	
Vapor pressure	<0.013 kPa [room temperature] Not applicable. [50°C]	
Vapor density	>2 [Air = 1]	
Relative density	0.865 to 0.885 [ISO 12185]	
Density	0.865 to 0.885 g/cm³ [15°C] [ISO 12185]	
Solubility(ies)		
Media	Result	
water	Not soluble	



SDS # :

090525

Miscible with water Partition coefficient: n-octanol/ water		No. Not applicable.	
Auto-ignition temperature	:	>210°C [ASTM E 659]	
Decomposition temperature	:	Not applicable.	
Viscosity	:	Kinematic (40°C): 40 to 52 mm ² /s [ASTM D 445]	
Particle characteristics			
Median particle size	:	Not applicable.	

9.2 Other information

No other relevant physical and chemical parameters for the safe use of the product

SECTION 10: Stability and reactivity

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: Stable under recommended storage and handling conditions (see Section 7).
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
10.5 Incompatible materials	: Strong oxidizing agents
10.6 Hazardous decomposition products	: Farbon monoxide carbon dioxide Silicon Dioxide nitrogen oxides phosphorus oxides Sodium oxides sulfur oxides Hydrogen sulfide Mercaptans Zinc oxides

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/substance	Result	Species	Dose	Exposure	Test
Polysulfides, di-tert-Bu	LD50 Dermal	Rat - Male, Female	>2000 mg/kg	-	OECD 402
	LDLo Oral	Rat - Male, Female	2000 mg/kg	-	OECD 401
Distillates (petroleum), hydrotreated heavy paraffinic	LC50 Inhalation Dusts and mists	Rat - Male, Female	>5 mg/l	4 hours	OECD 403 Read across
	LD50 Dermal	Rabbit - Male, Female	>5000 mg/kg	-	OECD 402 Read across
	LD50 Oral	Rat - Male, Female	>5000 mg/kg	-	OECD 401 Read across

Revision:2024/04/15	Version : 1.02	Romania	ENGLISH	10/19



SDS # :

090525

zinc 0,0,0',0'-tetrakis LC50 Inhalation Dusts Rat 5.1 mg/l 4 hours _ (1,3-dimethylbutyl) bis and mists (phosphorodithioate) LD50 Dermal Rabbit **OECD 402** >25000 mg/ kg LD50 Oral 2230 mg/kg **OECD 401** Rat Distillates (petroleum), LC50 Inhalation Dusts >5.53 mg/l 4 hours **OECD 403** Rat - Male. hydrotreated light paraffinic and mists Female Acute Inhalation Toxicity **OECD** 402 LD50 Dermal Rabbit - Male, >5000 mg/kg Female Acute Dermal Toxicity Rat - Male, >5000 mg/kg LD50 Oral **OECD 401** Female Acute Oral Toxicity oleic acid, compound with LD50 Dermal Rat >2000 mg/kg **OECD** 402 (Z)-N-octadec-9-enylpropane-1,3-diamine (2:1) LD50 Oral Rat **OECD 423** >2000 mg/kg

Acute toxicity estimates

Product/substance	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl) bis (phosphorodithioate)	2230	N/A	N/A	N/A	5.1

Conclusion/Summary : Based on available data, the classification criteria are not met.

Irritation/Corrosion

Product/substance	Result	Species	Score	Exposure	Test
Polysulfides, di-tert-Bu	Eyes - Cornea opacity Skin - Erythema/Eschar	Rabbit Rabbit	0 2	-	OECD 405 OECD 404
0					

Conclusion/Summary

Skin	: Based on available data, the classification criteria are not met.					
Eyes	: Based on available data, the classification criteria are met.					
Respiratory	: Based on available data, the classification criteria are not met.					
Sensitization						
Product/substance	Route of exposure	Species	Result			
Polysulfides, di-tert-Bu	skin	Guinea pig	Sensitizing			
Conclusion/Summary	I	Ι	1			

Skin

Respiratory : Based on available data, the classification criteria are not met.

: Based on available data, the classification criteria are not met.

Mutagenicity



SDS # : 090525

Product/substance	Test	Experiment	Result			
Polysulfides, di-tert-Bu	OECD 471	Experiment: In vitro	Negative			
		Subject: Bacteria				
	OECD 473	Experiment: In vitro	Negative			
		Subject: Mammalian-Animal				
	OECD 476	Experiment: In vitro	Negative			
	0505 474	Subject: Mammalian-Animal	NI			
	OECD 474	Experiment: In vivo	Negative			
		Subject: Mammalian-Animal				
Conclusion/Summary	: Based on available data, the classification criteria are not met.					
Carcinogenicity						
Conclusion/Summary	: Based on available dat	ta, the classification criteria are not m	et.			
Reproductive toxicity						
Conclusion/Summary	: Based on available data, the classification criteria are not met.					
Teratogenicity						
Conclusion/Summary	: Based on available data, the classification criteria are not met.					
Specific target organ toxicity	<u>y (single exposure)</u>					

Conclusion/Summary : Based on available data, the classification criteria are not met.

Specific target organ toxicity (repeated exposure)

Product/substance	Category	Route of exposure	Target organs
oleic acid, compound with (Z)-N-octadec-9-enylpropane- 1,3-diamine (2:1)	Category 2	-	-

Conclusion/Summary : Based on available data, the classification criteria are not met.

Aspiration hazard

Prod	uct/substance	Result			
	stillates (petroleum), hydrotreated heavy paraffinicASPIRATION HAZARD - Category 1stillates (petroleum), hydrotreated light paraffinicASPIRATION HAZARD - Category 1				
Conclusion/Summary	: Based on available data, the c	Based on available data, the classification criteria are not met.			
Information on the likely routes of exposure	: Not available.				
Potential acute health effect	ts				
Eye contact	: Causes serious eye irritation.				
Inhalation	: No known significant effects o	No known significant effects or critical hazards.			
Skin contact	: Defatting to the skin. May cau	Defatting to the skin. May cause skin dryness and irritation.			
Ingestion	: No known significant effects o	No known significant effects or critical hazards.			
Symptoms related to the ph	nysical, chemical and toxicologica	al characteristics			
Eye contact	: Adverse symptoms may includ pain or irritation watering redness	de the following:			
Inhalation	: No specific data.				
Skin contact	: Adverse symptoms may includ irritation dryness cracking	de the following:			



effects

: No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure						
<u>Short term exposure</u>						
Potential immediate effects	: Not available.					
Potential delayed effects	: Not available.					
<u>Long term exposure</u>						
Potential immediate	: Not available.					

Potential delayed effects : Not available. Potential chronic health effects

Product/substance	Result	Species	Dose	Exposure	
Polysulfides, di-tert-Bu	Sub-acute NOAEL Oral	Rat - Male, Female	100 mg/kg	-	
Conclusion/Summary	: Not available.				
General	: No known significant effects or critical hazards.				
Carcinogenicity	: No known significant effects or critical hazards.				
Mutagenicity	: No known significant effects or critical hazards.				
Reproductive toxicity	: No known significant effects or critical hazards.				

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

This product does not contain any substance present at a concentration equal to or greater than 0.1% by mass, included in the list drawn up in accordance with article 59, paragraph 1 of the REACh Regulation, due to its endocrine disrupting properties, or a substance known to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation 2018/605.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/substance	Result	Species	Exposure	Test
Polysulfides, di-tert-Bu	Acute EC50 >100 mg/l	Algae	72 hours	-
-	Acute EC50 63 mg/l	Daphnia - Daphnia magna	48 hours	-
Distillates (petroleum), hydrotreated heavy paraffinic	Acute EC50 >100 mg/l	Algae - Pseudokirchneriella	72 hours	OECD 201
	Acute EC50 >10000 mg/l	subcapitata Crustaceans - Daphnia magna	48 hours	OECD 202
	Chronic NOEL >100 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours	OECD 201
	Chronic NOEL >1000 mg/l	Crustaceans - Daphnia magna	21 days	-
zinc O,O,O',O'-tetrakis (1,3-dimethylbutyl) bis (phosphorodithioate)	Acute EC50 21 mg/l	Algae - Desmodesmus subspicatus	72 hours	OECD 201
(prooprior outerioute)	Acute EC50 23 mg/l Acute LC50 4.5 mg/l	Daphnia - <i>Daphnia magna</i> Fish	48 hours 96 hours	OECD 202 -
	Chronic NOEC 0.4 mg/l	Daphnia - Daphnia magna	21 days	OECD 211



SDS # :

090525

Distillates (petroleum), hydrotreated light paraffinic	Acute EC50 101 mg/l	Daphnia - <i>Daphnia magna</i>	48 hours	OECD 202
, 31	Acute LC50 101 mg/l	Fish	96 hours	-
oleic acid, compound with (Z)		Algae -	72 hours	OECD 201
-N-octadec-9-enylpropane-	, i i i i i i i i i i i i i i i i i i i	Pseudokirchneriella		
1,3-diamine (2:1)		subcapitata		
	Acute LC50 0.134 mg/l	Fish	96 hours	-
	Chronic EC10 0.032 mg/l	Algae	72 hours	OECD 201
	Chronic EC50 0.14 mg/l	Daphnia - Daphnia magna	21 days	OECD 211
Conclusion/Summary	: Not available.		•	

12.2 Persistence and degradability

Product/substance	Test	Result	Dose	Inoculum
Distillates (petroleum), hydrotreated heavy paraffinic		31 % - Not readily - 28 days	-	Activated sludge

Conclusion/Summary : Not available.

Product/substance	Aquatic half-life	Photolysis	Biodegradability
Polysulfides, di-tert-Bu Distillates (petroleum),	-	-	Not readily Not readily
hydrotreated heavy paraffinic zinc O,O,O',O'-tetrakis (1,3-dimethylbutyl) bis	-	-	Not readily
(phosphorodithioate) oleic acid, compound with	-	-	Readily
(Z)-N-octadec- 9-enylpropane-1,3-diamine (2:1)			

12.3 Bioaccumulative potential

Product/substance	LogKow	BCF	Potential
Polysulfides, di-tert-Bu	6	-	High
Distillates (petroleum),	>4	-	High
hydrotreated heavy paraffinic			
zinc 0,0,0',0'-tetrakis	2.21	-	Low
(1,3-dimethylbutyl) bis			
(phosphorodithioate)			
oleic acid, compound with	0.03	-	Low
(Z)-N-octadec-			
9-enylpropane-1,3-diamine			
(2:1)			

12.4 Mobility in soil	
Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.
Mobility in soil	: Given its physical and chemical characteristics, the product generally shows I mobility The product is insoluble and floats on water Loss by evaporation is

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB in a concentration >= 0,1 %.

low soil limited



12.6 Endocrine disrupting properties

This product does not contain any substance present at a concentration equal to or greater than 0.1% by mass, included in the list drawn up in accordance with article 59, paragraph 1 of the REACh Regulation, due to its endocrine disrupting properties, or a substance known to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation 2018/605.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods	
<u>Product</u>	
Methods of disposal	: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: Yes.
	According to the European Waste Catalogue, Waste Codes are not product specific, but application specific Waste codes should be assigned by the user based on the application for which the product was used. The following Waste Codes are only suggestions: 13 02 05*
<u>Packaging</u>	
Methods of disposal	: The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	ICAO/IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.



SDS #: 090525

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in : Not available. **bulk according to IMO instruments**

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>EU Regulation (EC) No. 1907/2006 (REACH)</u>

Annex XIV - List of substances subject to authorization

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

<u>Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous</u> <u>substances, mixtures and articles</u>

Other EU regulations

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Industrial emissions (integrated pollution prevention and control) - Air	:	Listed
Industrial emissions (integrated pollution prevention and control) - Water	:	Not listed
Explosive precursors	:	Not applicable.
Ozone depleting substance	s	<u>(1005/2009/EU)</u>

Not listed.

Prior Informed Consent (PIC) (649/2012/EU) Not listed.

Persistent Organic Pollutants Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

National regulations

National regulatory information



SDS #: 090525

GD 398/2010 on establishing measures for application of Regulation (EC) no. 1.272 / 2008 of the European Parliament and of the Council of 16 December 2008 on classification, labeling and packaging of substances and mixtures, amending and repealing Directives 67/548 / EEC and 1999/45 / EC, and amending Regulation (EC). 1.907 / 2006GD 477/2009 on establishing penalties for infringements of the provisions of Regulation (EC) no. 1.907 / 2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Agency for Chemicals, amending Directive 1999/45 / EC and repealing Regulation (EC) No . 793/93 and Regulation (EC) no. 1,488 / 94 Commission and Council Directive 76/769 / EEC and Directives 91/155 / EEC, 93/67 / EEC, 93/105 / EC and 2000/21 / EC of the CommissionGD 1218/2006 laying down minimum requirements for safety and health at work for the protection of workers from risks related to chemical agents

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC) Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

LU - Luxembourg prohibited chemicals in the workplace

Not listed.

.. .

Inventory list	
Australia inventory (AIIC)	: All components are listed or exempted.
Canada inventory (DSL/NDSL)	: All components are listed or exempted.
China inventory (IECSC)	: All components are listed or exempted.
Europe inventory (EC)	: All components are listed or exempted.
Japan inventory	 Japan inventory (CSCL): All components are listed or exempted. Japan inventory (ISHL): All components are listed or exempted.
New Zealand Inventory of Chemicals (NZIoC)	: All components are listed or exempted.
Philippines inventory (PICCS)	: At least one component is not listed.
Korea inventory (KECI)	: All components are listed or exempted.
Taiwan Chemical Substances Inventory (TCSI)	: All components are listed or exempted.
Thailand inventory	: Not determined.
Turkey inventory	: Not determined.
United States inventory (TSCA 8b)	: All components are listed or exempted.
Vietnam inventory	: Not determined.
The information stated in this section relates so	lely to the conformity of the chemical product with the

The information stated in this section relates solely to the conformity of the chemical product with the countries Inventories. The information used to confirm the inventory status of this product may be based on additional data to the chemical composition shown in Section 3. Other regulations may apply for importation or marketing authorizations.

15.2 Chemical Safety: Risk management measures and safety conditions of use are included in the
relevant sections of the SDS



SDS #: 090525

SECTION 16: Other information

	hat has changed from previously issued version.
Abbreviations and	: ACGIH = American Conference of Governmental Industrial Hygienists
acronyms	ATE = Acute Toxicity Estimate
	BCF = Bioconcentration Factor
	CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.
	1272/2008]
	DNEL = Derived No Effect Level
	DMEL = Derived Minimal Effect Level
	DMSO = Dimethyl Sulfoxide
	EL50 = median Effective Loading
	EUH statement = CLP-specific Hazard statement
	HSE = Health, Safety and Environment
	IC50 = Half maximal inhibitory concentration
	IDHL = Immediately dangerous to life or health
	LC50 = Median lethal concentration
	LD50 = Median lethal dose
	LL50 = median Lethal Loading
	LogPow = logarithm of the octanol/water partition coefficient
	N/A = Not available
	NIOSH = National Institute of Occupational Safety and Health
	NOAEL = No Observed Adverse Effect Level
	NOEC No Observed Effect Concentration
	NOEL = No Observed Effect Level
	NOELR = No observed Effect Loading Rate
	OECD = Organisation for Economic Co-operation and Development
	OEL = Occupational Exposure Limit
	PBT = Persistent, Bioaccumulative and Toxic
	PNEC = Predicted No Effect Concentration
	QSAR = Quantitative Structure–Activity Relationship
	REL = Recommanded Exposure Limit
	STEL = Short Term Exposure Limit
	TLV = Threshold Limit Value
	TWA = Time Weight Average
	VOC = Volatile Organic Compound
	vPvB = Very Persistent and Very Bioaccumulative
	Unique Formula Identifier (UFI)
	UVCB Substance of unknown or Variable composition, Complex reaction products
	or Biological material
	a the closeffication according to Degulation (EC) No. 1979/2008 [CLD/CLB]

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Eye Irrit. 2, H319	Calculation method

Full text of abbreviated H statements

H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H373	May cause damage to organs through prolonged or repeated
	exposure.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Full text of classifications [CLP/GHS]



SDS #: 090525

Aquatic Acute 1	AQUATIC HAZARD (ACUTE) - Category 1
Aquatic Chronic 2	AQUATIC HAZARD (LONG-TERM) - Category 2
Aquatic Chronic 3	AQUATIC HAZARD (LONG-TERM) - Category 3
Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Eye Dam. 1	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1B	SKIN SENSITIZATION - Category 1B
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY (REPEATED
	EXPOSURE) - Category 2

Date of revision	: 2024/04/15
previous revision date	: 2023/08/03
Version	: 1.02

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.