

Agritraite 68

Milking machine vacuum pumps oil

KEY DATA



Lubricant specifically developed for specific vacuum pumps used in milking machines.

APPLICATIONS

Agritraite is suitable for the lubrication of specific vacuum pumps used in milking machine:

- 🔥 Vane pumps
- 🔥 Screw pumps
- 🔥 Roots pumps

PERFORMANCES & CUSTOMERS BENEFITS

Agritraite exhibits lots of properties:

- 🔥 No shear
- 🔥 Very good anti-wear properties
- 🔥 Anti-corrosion, anti-rust, anti-foam properties
- 🔥 No air retention
- 🔥 Excellent desemulsibility
- 🔥 Very good seal compatibility

CHARACTERISTICS*

TEST	UNIT	TEST METHOD	RESULT
Density at 15°C	kg/m ³	ASTM D1298	884
Kinematic viscosity at 40°C	mm ² /s	ASTM D445	68
Kinematic viscosity at 100°C	mm ² /s	ASTM D445	8.7
Viscosity index	-	ASTM D2270	100
Pour point	°C	ASTM D97	-21

*The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

RECOMMENDATIONS FOR USE

Before using the product, the vehicle's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations. If possible, the packaging should not be exposed to the elements. Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

HEALTH, SAFETY AND THE ENVIRONMENT

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet (SDS).

This can be obtained on request from your local reseller and is available for consultation at <https://ms-sds.totalenergies.com>.

This product should not be used for any purposes other than the ones for which it is intended.

