

linelube CVT (Continuous Variable Transmission) Fluid

Product Description

linelube CVT Fluid is a synthetic based lubricant designed specifically for the new generation of automatic Continuous Variable Transmissions of all vehicle manufacturers including Fiat, Ford and Volvo. CVT Fluid is based on synthetic stocks plus anti wear, anti-foam and antioxidant additives. CVT Fluid also contains a friction modifier, viscosity index improver and pour point depressant.

Features & Benefits

- Anti-wear, anti-foam and antioxidant additives.
- Longer drain periods
- Effective foam control
- Superior wear protection
- Excellent thermal protection

Applications

All automatic Continuous Variable Transmission units. Also, other ATF applications where extremely high temperatures are present, and using mineral oil-based products can cause performance problems. CVT Fluid will provide much longer drain periods without loss of crisp shift feel.

Specifications

Linelube CVT fluids meets the requirements of:

- Toyota CVTF TC
- Toyota CVTF FE
- Nissan NS-1,2,3
- Honda HMMF *1)
- Honda HCF2
- Mitsubishi SP-III
- Mitsubishi CVTF-J1
- Mazda JWS 3320
- Subaru Lineartronic HT Chain CVT
- Daihatsu Ammix CVT
- Suzuki NS-2 Suzuki CVT Green 1&2
- Suzuki CVTF TC
- Hyundai SP-III (CVT Model)
- Chrysler Jeep NS-2/CVTF +4
- GM DEX CVT
- Mini Cooper EZL799

Typical Test Data

Colour	Dark Red
Viscosity Index	179
Kinematic Viscosity @ 40°C (cSt)	33.98
Kinematic Viscosity @ 100°C (cSt)	7.11

Health & Safety

For health and safety information please refer to the relevant health & safety data sheet on our website. The contents of this data sheet are given in good faith but without warranty.